

## Vibro-Meter Corp

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Vibro-Meter Corp** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Vibro-Meter Corp T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Lb 217/Sxxx 220kn Specialitem</a>	122-217-000Sxxx Compatible successor to LB192S042 Special load measuring pin Diameter 70h6, // Nominal load 220kN X-Y version 2x cable K - 414, length 5m, PG radial Steel 1.4418 // Degree of protection: IP 66
<a href="#">Lb 216/Sxxx 110kn Specialitem</a>	122-216-000Sxxx Compatible successor to LB190S076 Special load measuring pin Diameter 50h6, // Nominal load 110kN Cable K - 414, length 5m, PG radial Steel 1.4418 // Degree of protection: IP 66
<a href="#">Pnr 244-707-000-012</a>	Charge amplifier / integrator IPC 707 PNR 244-707-000-012 Environment (A) 2: Explosive (Ex i) Diagnostics (B) 1: Without diagnostic Transfer sensitivity (C) 2: 2 Transfer units (D) 1: without integrator in uA / pC HP filter (E) 2: 2 Hz LP filter (F) 10000: 10,000 Hz Installation (G) 1: Without rail DIN adapter according to Data sheet DS 262-712 Vers. 5 from 07/08/2019 Net weight (Ex version): approx. 0.250 kg / piece EU / dt. Right: N // US law: N stat. Lot number: 90319000 CH Attachment for delivery: 10 x test report (English) Annotation: Replacement for IPC 704 (PNR 144-704-000-012)
<a href="#">Type ABE 022</a>	Rack for the PERMODULE System

<a href="#">Type UVV 696</a>	Relative Vibration Processor
<a href="#">Type PLD 772</a>	Level Detector and Display
<a href="#">Type UVL 682</a>	Phase Reference Processor
<a href="#">Type APF 184</a>	DC/DC Converter
<a href="#">Type IQS 452</a>	Signal Conditioner Matched with TQ402, Sens: 4 mv/ $\mu$ m, Cable Length: 5 m
<a href="#">Type TQ 402</a>	Proximity Transducer Cable : 5 m Generator NDS
<a href="#">204-017-400 Series &amp; 204-093-400 series Connector</a>	Rectangular Connector 56 Poles, Part Number: 957.12.07.7101 Male plug Unit Control Panel Cubicle