



Vipa

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin

info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Vipa Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Vipa Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
253-1dp01	M 253DP - Profibus-DP slave DC 24V, 12Mbit / s, address 1 ... 99, DP-V0, DP-V1, Configuration via GSD file from VIPA, up to 32 modules
231-1bd53	SM 231 - Analoge Eingabe AI 4x16Bit, U, I, R, TC, RTD
221-1bf00	SM 221 - digital input DI 8xDC 24V
222-1bf00	SM 222 - digital output DO 8xDC 24V, 1A
232-1bd51	SM 232 - analog output AO 4x12Bit, U, I
315-2ag23	* powered by SPEED7 * RAM [KB]: 1,024 - 4,096 * Interface [RJ45]: Ethernet PG / OP communication * Interface [2x RS485]: MPI, PROFIBUS master / slave, PtP: ASCII, STX / ETX, 3964 (R), USS Master, Modbus Master / Slave * SD / MMC card slot with locking, up to 32 modules can be added, programmable via SPEED7 Studio, SIMATIC Manager and TIA Portal
221-1FF50	Vipa SM 221 - digital input
MISIP-REM-YVP-972-ODP10	
053-1PN00	
001-1BA00	
001-1BA10	

021-1BF00	
022-1BF00	
007-1AB00	
031-1BF60	SM 031 - Analog input 8x AI single-ended (reference potential 0V) 12 bits Current 0(4)...20mA Individually configurable inputs Electrically isolated from the backplane bus
232-1BD51	Vipa SM 232 - analog output AO 4x12Bit, U, I 85176990 - TH - 0.2 kg
007-06AA00	
021-1BF00	
022-1BF00	
001-00AA00	
053-1DP00	Vipa 053-1DP00 / bearing IM 053DP - Profibus DP slave DC 24V, 12Mbit / s, address 1 ... 125, DP-V0, DP-V1, Configuration via GSD file from VIPA, up to 64 modules 85176990 - TH - 0.1 kg
232-1BD30	SM 232 - Analog output ECO 4x AO 12 Bit Voltage 0...10 V, +/- 10 V Parameterizable
317-4PN23	VIPA CPU 317PN Powered by SPEED7 Work memory [KB]: 8MB Integrated PROFINET controller SPEED-Bus Interface [RJ45]: PROFINET Interface [RJ45]: Ethernet PG/OP communication Interface [RS485]: MPI Interface [RS485]: PROFIBUS master/slave, PtP: ASCII, STX/ETX, 3964(R), USS master, Modbus master/slave SD/MMC card slot with locking, up to 32 modules stackable, programmable with WinPLC7, SIMATIC Manager and TIA Portal
1.0390-1AB60	Profile rail Length: 160 mm
911-2PN50	VIPA managed Industrial-Switch PN5-RD 5x RJ45 10/100BaseTX full-/half duplex, automatic MDI/MDI-X recognition PROFINET v2 Conformance Class B, PROFINET diagnosis via GSD integration Assurance of service quality, based on IEEE 802.1p and TOS/DiffServ, improves the deterministic operation Management functions such as IGMP Snooping, IEEE 802.1Q VLAN, QoS, Port Mirroring, SNMP, broad band management, and warning message by E-Mail or relay output DHCP option 82 for IP address allocation with different allocation rules Short boot times and recovery technologies Turbo Ring™ and Turbo Chain™ Redundant power supply for DC 24 V IP30 aluminium case for DIN rail mounting (wall mounting kit optional)
	IM 053PN - PROFINET-IO slave Integrated 2-port switch Up to 64 peripheral modules Transfer rate 100Mbit/s full-duplex Supports MRP slave as MRP client, FMM (Free Module Mapping), Easy Maintenance Supports shared device with up to 3 connections Supports IRT (Isochronous Real Time

053-1PN01	communication) Supports multiple and single write (acyclic communication) Integrated Web server Integrated DC 24V power supply for power and electronic section supply of the periphery modules Status LEDs
032-1CD70	SM 032 - Analog output 4x AO 16 bits Voltage -10V...+10V
1.0031-1CD40	SM 031 - Analog input 4x AI 16 Bit Current 0(4)...20 mA
1.0021-1BF00	SM 021 - Digital input 8x DI DC 24 V
1.0022-1BF00	SM 022 - Digital output 8x DO DC 24 V 0.5 A
MISIP-REM-YVP-972-ODP10	
0022-1BF00	SM 022 - Digital output 8x DO DC 24 V 0.5 A
021-1BF00	SAP#: 100-220-800 SM 021 - Digital input 8x DI DC 24 V
022-1BF00	SM 022 - Digital Edition 8x THU DC 24V 0.5A
VIPA CPU 013C (013-CCF0R00)	
SM 031	031-1CA20 Analog input Direct connection of a full resistance bridge (DMS) or load cells 4- or 6-wire connection 16 (24) bit resolution Auto/self-calibration zero and span Absolute Accuracy Basic Error $\pm 0.1\%$ ($\pm 0.01\%$) Onboard power supply 2V5, 5V, 7V5, 10V and 12V
CPU 014	014-CEF0R01 Powered by SPEED7 Main memory [KB]: 128...256 Integrated PROFINET Controller (limited to 8 devices) / I-Device Interface [1x RJ45]: PROFINET, ModbusTCP master/slave, open communication Interface [1x RJ45]: active Ethernet PG/OP communication with DHCP support, switch Interface [2x RS485]: MPI, PtP: ASCII, STX/ETX, 3964(R), USS Master, Modbus Master/Slave Optional: PROFIBUS master/slave Web servers SD card slot with locking, expandable up to 64 modules, programmable via SPEED7 Studio, SIMATIC Manager and TIA Portal OPC UA available from hardware version 2
SM 021	021-1BF00 digital input 8x TUE DC 24V
SM 022	022-1BF00 Digital input 8x THU DC 24V 0.5A
VIPA unmanaged industrial switch EN5-R 910-1EN50	5x RJ45 10/100BaseTX full/half duplex Supports IEEE 802.3 and IEEE 802.3u/x and automatic MDI/MDI-X detection Redundant power supply for DC 12-45 V IP30 aluminum housing for DIN rail mounting (wall mounting kit optional)
CPU 015PN 015-CEFPR01	Powered by SPEED7 Main memory [KB]: 256...512 Integrated PROFINET controller / I device Interface [2x RJ45]: PROFINET, ModbusTCP Master/Slave, openCommunication Interface [2x RJ45]: active Ethernet PG/OP communication with DHCP support, switch Interface [2x RS485]: MPI, PtP: ASCII, STX/ETX, 3964(R), USS Master, Modbus Master/Slave Optional: PROFIBUS master/slave Web servers SD card slot with locking, expandable up to 64 modules, programmable via SPEED7 Studio, SIMATIC Manager and TIA Portal OPC UA

	available from hardware version 2
SM 031 - Analog input 031-1BF60	8x AI single-ended (reference potential 0V) 12 bits Current 0(4)...20mA Individually configurable inputs Electrically isolated from the backplane bus
972-ODP10	EasyConn 90° - PROFIBUS connector Clock rates up to 12 Mbit/s metal body PG socket Switchable terminating resistor 90° cable outlet Bus diagnostics via LEDs
972-ODP30	EasyConn 0° - PROFIBUS connector Clock rates up to 12 Mbit/s metal body Switchable terminating resistor 0° cable outlet Bus diagnostics via LEDs
972-ODP01	EasyConn 90° - PROFIBUS connector Clock rates up to 12 Mbit/s metal body PG socket Switchable terminating resistor 90° cable outlet
022-1bf00 digital output	
221-1BF00	SM 221 - Digital input 8x DI DC 24 V
231-1BD53	SM 231 - Analog input 4x AI 16 bits Voltage current Resistance thermometer, thermocouple Configurable
222-1BF00	SM 222 - Digital Edition 8x DO DC 24 V 1 A
253-1DP01	IM 253DP - PROFIBUS-DP-Slave DC 24V 12 Mbps Configuration via GSD file from VIPA Up to 32 modules (16 analogue) 244 bytes input and 244 bytes output data
321-1BL00	SM 321 - Digital input 4x SDI DC 24V Safety / PROFIsafe
972-ODP01	EasyConn 90° - PROFIBUS connector Clock rates up to 12 Mbit/s metal body PG socket Switchable terminating resistor 90° cable outlet Packing unit: 1 piece
332-5HD01	SM 332 - analog output 4x AO 16 bits Current 0(4)...20mA
CPU CPU 314 ST	
IM 053DP ADRES MOD¼L 053-1DP00	
DI 8XDC24V DİJİTAL İNPUT 021-1BF00	
AI 4X12BİT ANALOG İNPUT 0-10 VOLT 031-1BD30	
AI 4X12BİT ANALOG İNPUT 4-20mA 031-1BD40	
AI4X16BİT RTD ANALOG İNPUT PT100 031-1BD80	
031-1CD40	SM 031 - Analog input 4x AI 16 bits Current 0(4)...20mA
021-1BH00	Digital card 16 DI 16xDC 24V
022-1BH00	SM 022 - Digital Edition 16x THU DC 24V 0.5A

SM 021 - Digital input	021-1BF00 8x DI DC 24 V
SM 022 - Digital Edition	022-1BF00 8x DO DC 24 V 0,5 A
SM 031 - Analog input	031-1BD30 4x AI 12 Bit Spannung 0...10 V
SM 032 - Analog output	032-1BD70 4x AO 12 Bit Spannung -10 V...+10 V
PM 007 - power module	007-1AB00 output supply Supply voltage DC 24 V 10A reverse polarity protection Overvoltage protection
EasyConn 90° - PROFIBUS-Stecker	972-ODP10 EasyConn 90° - PROFIBUS plug Clock rate up to 12 Mbit/s Metal case PG jack Switchable terminating resistor 90° outgoing cable Bus diagnosis via LEDs Packing unit: 1 piece
EasyConn 0° - PROFIBUS-Stecker	972-ODP30 Clock rates up to 12 Mbit/s metal body Switchable terminating resistor 0° cable outlet
SM 022 - Digital Edition	022-1BF00 SM 022 - Digitale Ausgabe 8x DO DC 24 V 0,5 A
EasyConn 45° - PROFIBUS connector	972-ODP20 Clock rates up to 12 Mbit/s metal body PG socket Switchable terminating resistor 45° cable outlet Bus diagnostics via LEDs
EasyConn 90° - PROFIBUS connector	972-ODP10 EasyConn 90° - PROFIBUS plug Clock rate up to 12 Mbit/s Metal case PG jack Switchable terminating resistor 90° outgoing cable Bus diagnosis via LEDs Packaging unit: 1 piece
CPU 314SE	314-2BG23 VIPA CPU 314SE Type : 314SE, Powered by SPEED7 Device Family : 300S+ Rated voltage : DC 20.4...28.8 V RAM : 256...1,024 kB onboard digital : -- DI/ -- DO/ -- DIO onboard analogue : -- AI/ -- AO interfaces - RJ45 (1x) : Ethernet PG/OP communication - RS485 (2x) : MPI, PROFIBUS Slave, PtP: ASCII, STX/ETX, 3964(R), USS Master, Modbus Master/Slave - SD/MMC slot : with locking expandable : - up to 32 modules can be added programmable : - via WinPLC7, SIMATIC Manager and TIA Portal
972-ODP10	EasyConn 90° - PROFIBUS connector with diagnostic LEDs EasyConn 90° - PROFIBUS connector Clock rates up to 12 Mbit/s metal body PG socket Switchable terminating resistor 90° cable outlet Bus diagnostics via LEDs
IM 253DP - PROFIBUS-DP-Slave 253-1DP01	Art. 00028658 DC 24V 12 Mbps Configuration via GSD file from VIPA Up to 32 modules (16 analogue) 244 bytes input and 244 bytes output data
teleservicemodule 900-2C510	
SM 021 - digital input, SLIO 021-1BF00	SLIO input module Version : 8 digital inputs, DC 24V
SM 031 - Analog input 031-1LD80	SM 031 - Analog input 4x AI 16 bits Resistance 0...3000 ohms Resistance measurement 2-, 3-, and 4-wire Resistance temperature sensors Pt100, Pt1000, NI100 and NI1000 Reduced parameter bytes
SM 031 - analog input, SLIO 031-1BD40	input module Type : SM 031 Version : 4 analogue inputs, 12 bit Current 0 (4)...20mA

smartPanel TP310-SM HA1-71A41-0	Display: 10.1" Processor: Cortex-A8 1GHz Memory [MB]: 512 User memory [GB]: 4 Onboard interface: 1x RS232/422/485 1x USB A 1x RJ45 (Ethernet) Software: Windows Embedded Compact 7 Movicon CE standard
EC71330	Cosy 131 Cosy+ ETH Router For remote maintenance via Talk2M VPN 4x RJ45 LAN 100 Mbit/s (integrated switch, configurable LAN/WAN) 2x digital input for Internet / VPN release 1x digital output for Talk2M display Integrated web interface for configuration SD card slot USB interface for connecting serial devices Certificates: CE, cULus listed, FCC WIFI characteristics: WAN connection: Ethernet or WiFi 802.11 b/g/n Frequencies: Channels: 1 to 11(inclusive) Security: WPA2, WPA and WEP Antenna connector: RP-SMA female connector Antenna: included; Frequency: 2.4GHz; Impedance: 50 ohms; Gain: 2.0dBi
IM 053PN - PROFINET-IO-Slave	053-1PN01 2-port switch integrated Up to 64 peripheral modules Transmission rate 100MBit/s full duplex Supports MRP slave as MRP client, FMM (Free Module Mapping), Easy Maintenance Supports shared devices with up to 3 connections Supports IRT (Isochronous Real-Time Communication) Supports multiple and single write (acyclic communication) Integrated web server Integrated DC 24V power pack for the electronics and power supply of the peripheral modules LEDs for status indication
SM 032 - Analog output	00028518 4x AO 12 bits Voltage 0...10V
SM 031 - Analog input	SM 031 - Analog input 4x AI 12 bits Voltage 0...10V 00028494
IM 053PN - PROFINET-IO-Slave	053-1PN01 IM 053PN - PROFINET IO slave 2-port switch integrated Up to 64 peripheral modules Transmission rate 100MBit/s full duplex Supports MRP slave as MRP client, FMM (Free Module Mapping), Easy Maintenance Supports shared devices with up to 3 connections Supports IRT (Isochronous Real-Time Communication) Supports multiple and single write (acyclic communication) Integrated web server Integrated DC 24V power pack for the electronics and power supply of the peripheral modules LEDs for status indication
SM 031 - Analog input	031-1BD30 SM 031 - Analog input 4x AI 12 bits Voltage 0...10V
SM 031 - Analog input	031-1BB60 SM 031 - Analog input 2x AI 12 bits Current 0(4)...20mA 2 wire
SM 022 - Digital Edition	022-1BF00 SM 022 - Digitale Ausgabe 8x DO DC 24 V 0,5 A
SM 022 - Digital Edition	022-1BD20 SM 022 - Digitale Ausgabe 4x DO DC 24 V 2 A
FM 050 - counter module	050-1BA00 FM 050 - counter module 1x counter 32 bits (AB), DC 24 V Up to 400kHz 1x DO, DC 24 V 0.5A
FM 050 - counter module	050-1BB00 FM 050 - counter module 2x counters 32 bits (AB), DC 24 V Up to 400kHz
	EasyConn 90° - PROFIBUS connector Clock rates up to 12

972-ODP10	Mbit/s metal body PG socket Switchable terminating resistor 90° cable outlet Bus diagnostics via LEDs
SM 231 - Analog input	231-1BD53 4x AI 16 bits Voltage current Resistance thermometer, thermocouple Configurable
CPU015 CPU	015-CEFP01 Powered by SPEED7 Main memory [KB]: 256...512 Integrated PROFINET controller / I device Interface [2x RJ45]: PROFINET, ModbusTCP Master/Slave, openCommunication Interface [2x RJ45]: active Ethernet PG/OP communication with DHCP support, switch Interface [2x RS485]: MPI, PtP: ASCII, STX/ETX, 3964(R), USS Master, Modbus Master/Slave Optional: PROFIBUS master/slave Web servers SD card slot with locking, expandable up to 64 modules, programmable via SPEED7 Studio, SIMATIC Manager and TIA Portal OPC UA available from hardware version 2
SM 021	021-1BF01 8x DI DC 24 V
SM 022 - Digital Edition	022-1BF00 SM 022 - Digitale Ausgabe 8x DO DC 24 V 0,5 A
SM 031 - Analog input	031-1CD40 SM 031 - Analoge Eingabe 4x AI 16 Bit Strom 0(4) ...20 mA
SM 032 - Analog output	032-1CD40 SM 032 - Analoge Ausgabe 4x AO 16 Bit
SM 331 - Analog input	331-1KF01 8x AI 12 bits Voltage +/- 10 V, +/- 50 mV, +/- 500 mV, +/- 5 V, 0 V ... +10 V Current +/- 20mA, 0/4...20mA Resistance thermometer, thermocouple For 40 pin front connector
IM 053DN - DeviceNet-Slave	353-1DP01 8x RJ45 10/100BaseTX full/half duplex, automatic MDI/MDI-X detection PROFINET v2 Conformance Class B, PROFINET diagnostics via GSD integration Quality of Service Assurance based on IEEE 802.1p and TOS/DiffServ improves the deterministic operation Management functions such as IGMP snooping, IEEE 802.1Q VLAN, QoS, port mirroring, SNMP, bandwidth management, and alerts via email or relay output DHCP option 82 for IP address assignment with different assignment rules Fast boot times and Turbo Ring™ and Turbo recovery technologies Chain™ Redundant power supply for DC 24 V IP30 aluminum housing for DIN rail mounting (wall mounting kit optional)
PS 307 - power pack	307-1EA00 100 Stück For safe coding of the SLIO module
VIPA CPU 314SE	314-2BG23 VIPA CPU 314SE Type : 314SE, Powered by SPEED7 Device Family : 300S+ Rated voltage : DC 20.4..28.8 V Main memory: 256..1,024 kB onboard digital : -- DI/ -- DO/ -- DIO onboard analogue : -- AI/ -- AO Interfaces... ..RJ45 (1x) : Ethernet PG/OP communication ...RS485 (2x) : MPI, PROFIBUS Slave, PtP: ASCII, STX/ETX, 3964(R), USS Master, Modbus Master/Slave ...SD/MMC slot : with lock expandable : - up to 32 modules can be added programmable : - via WinPLC7, SIMATIC Manager and TIA Portal
EasyConn 45° - PROFIBUS connector	972-ODP20 Clock rates up to 12 Mbit/s metal body PG socket Switchable terminating resistor 45° cable outlet Bus diagnostics via LEDs

CPU 215DPM	215-2BM03 VIPA CPU 215DPM Memory [KB]: 128 Interface [RS485]: MPI Interface [RS485]: PROFIBUS-DP master MMC card slot, expandable up to 32 modules Programmable via WinPLC7 and SIMATIC Manager
VIPA CPU 313SC	313-5BF23 VIPA CPU 313SC Powered by SPEED7 Work memory [KB]: 256...1,024 Onboard 24x DI / 16x DO / 5x AI [current/voltage] / 2x AO / 1x Pt100 / 3x counter / 3x PWM Interface [RJ45]: Ethernet PG/OP communication Interface [2x RS485]: MPI, PtP: ASCII, STX/ETX, 3964(R), USS master, Modbus master/slave Including front connector SD/MMC card slot with locking, up to 8 modules stackable, programmable with WinPLC7, SIMATIC Manager and TIA Portal
VIPA CPU 214	214-1BA03 VIPA CPU 214 Memory [KB]: 96 Interface [RS485]: MPI MMC card slot, expandable up to 32 modules Programmable via WinPLC7 and SIMATIC Manager 00028688
972-ODP10	EasyConn 90° - PROFIBUS connector w. Diagnostic LEDs EasyConn 90° - PROFIBUS connector Clock rates up to 12 Mbit/s metal body PG socket Switchable terminating resistor 90° cable outlet Bus diagnostics via LEDs Packing unit: 1 piece Goods tariff number: 85366990
SM 238C	digital input/output, counter, Analogue input/output Item 00028576 238-2BC00 16 (12)x DI, DC 24V 0 (4)x DO, DC 24 V, 1 A Max 3x counters up to 30 kHz 4x AI 12 bit 3x voltage, current 1x RTD 2x AO 12 bits voltage, current Goods tariff number: 85389099
SM 222	Digital edition Item 00028605 222-1BH10 16x THU DC 24V 1A Total current up to 10 A Goods tariff number: 85389099
SM 221	digital input Item 00028579 221-2BL10 32x TUE DC 24V Goods tariff number: 85389099
SM 221-2BL10	221-2BL10 32x DI DC 24 V
VIPA CPU 115	115-6BL04 Micro-SPS CPU 115 - Micro PLC 16 (20) inputs, 16 (12) outputs, from which are 2 PWM 50 kHz outputs, 32 kB work memory, 40 kB load memory
SM 222-1BF10	8x DO DC 24 V 2 A
EasyConn 90° - PROFIBUS connector	972-ODP01 00028632 EasyConn 90° - PROFIBUS connector Clock speeds up to 12 Mbit/s Metal case PG socket Switchable terminating resistor 90° cable outlet
VIPA CPU 315PN	315-4PN23 VIPA CPU 315PN Powered by SPEED7 Work memory [KB]: 1.024...4.096 Integrated PROFINET controller Interface [RJ45]: PROFINET Interface [RJ45]: Ethernet PG/OP communication Interface [RS485]: MPI Interface [RS485]: PROFIBUS master/slave, PtP: ASCII, STX/ETX, 3964(R), USS master, Modbus master/slave SD/MMC card slot with locking, up to 32 modules stackable, programmable with WinPLC7, SIMATIC Manager and TIA Portal
EasyConn 90° - PROFIBUS	972-ODP01 EasyConn 90° - PROFIBUS connector Clock speeds up to 12 Mbit/s Metal case PG socket Switchable terminating

	resistor 90° cable outlet
231 - 1BD53	4x AI 16 bits Voltage current Resistance thermometer, thermocouple Parameterizable SM 231 - Analog input
053-1PN01 IMO53 PN	
007-0AA00 PM007	10A 24VDC
021-1BF00 DI 8X DC-24V	
032,1BD40 AO 4X12 BİT 0/4.. 20mA	
031-1BD40 AI 4X12 BİT 0/4.. 20mA analog	input Modul
015-CEFP00 CPU 015PN	
SM 032 - Analog output, SLIO	032-1BD40
SM 031 - Analog input, SLIO	031-1BD40
CPU 015PN	015-CEFP01 Powered by SPEED7 RAM [KB]: 256...512 Integrated PROFINET controller / I-Device Interface [2x RJ45]: PROFINET, ModbusTCP Master/Slave, openCommunication Interface [2x RJ45]: active Ethernet PG/OP communication with DHCP support, switch Interface [2x RS485]: MPI, PtP: ASCII, STX/ETX, 3964(R), USS Master, Modbus Master/Slave Optional: PROFIBUS master/slave Web servers SD card slot with lock, expandable up to 64 modules, programmable via SPEED7 Studio, SIMATIC Manager and TIA Portal OPC UA available from hardware version 2
IM 053PN - PROFINET-IO-Slave	053-1PN01 IM 053PN - PROFINET IO slave 2-port switch integrated Up to 64 peripheral modules Transfer rate 100MBit/s full duplex Supports MRP slave as MRP client, FMM (Free Module Mapping), Easy Maintenance Supports shared devices with up to 3 connections Supports IRT (Isochronous Real-Time Communication) Supports multiple and single write (acyclic communication) Integrated web server Integrated DC 24V power supply for electronics and power supply of the peripheral modules LEDs for status display
PM 007 - Power-Modul	007-0AA00 Supply voltage DC 24 V (Only electronic module as a spare part for CPU and fieldbus module)
SM 021 - Digitale Eingabe, SLIO	021-1BF00 SLIO input module Type: SM 021 Version: 8 digital inputs, DC 24V
SM 032 - Analoge Ausgabe, SLIO	032-1BD40 Output module Type: SM 032 Version: 4 analog outputs, 12 bit Current 0 (4)...20mA
SM 031 - Analoge Eingabe, SLIO	031-1BD40 Input module Type: SM 031 Version: 4 analog inputs, 12 bit
	015-CEFP01 Powered by SPEED7 Arbeitsspeicher [KB]: 256...512 Integrierter PROFINET Controller / I-Device Interface [2x RJ45]: PROFINET, ModbusTCP Master/Slave, openCommunication Interface [2x RJ45]: aktive Ethernet PG/OP-Kommunikation mit DHCP Support, Switch Interface

CPU 015PN	[2x RS485]: MPI, PtP: ASCII, STX/ETX, 3964(R), USS Master, Modbus Master/Slave Optional: PROFIBUS Master/Slave Web Server SD-Karten-Slot mit Verriegelung, bis zu 64 Module erweiterbar, programmierbar ber SPEED7 Studio, SIMATIC Manager und TIA Portal OPC UA verfgbar ab Hardware Version 2
EasyConn 90° - PROFIBUS connector	Diagnostic LEDs Item 00028631 972-0DP10 EasyConn 90° - PROFIBUS connector Clock speeds up to 12 Mbit/s Metal case PG socket Switchable terminating resistor 90° cable outlet Bus diagnostics via LEDs
972-0DP10	
973-5BE00	B5+R 17020R
VIPA CPU 215DPM	215-2BM03 VIPA CPU 215DPM Memory [KB]: 128 Interface [RS485]: MPI Interface [RS485]: PROFIBUS-DP master MMC card slot, expandable up to 32 modules Programmable via WinPLC7 and SIMATIC Manager
CPU 315SN	315-4NE23 VIPA CPU 315SN Powered by SPEED7 Work memory [KB]: 1,024...4,096 Integrated Ethernet CP343 Lean Interface [RJ45]: Ethernet PG/OP communication Interface [RJ45]: active Ethernet CP343 & PG/OP communication Interface [RS485]: MPI Interface [RS485]: PROFIBUS master/slave, PtP: ASCII, STX/ETX, 3964(R), USS master, Modbus master/slave SD/MMC card slot with locking, up to 32 modules stackable, programmable with WinPLC7, SIMATIC Manager and TIA Portal
SM 234 - Analog input/output	234-1BD50 2x AI 2x AO 12 bits Voltage +/- 10 V, 1...5 V, 0...10 V Current +/- 20 mA, 0/4...20 mA Parameterizable
SM 223 - Digital input/output	223-1BF00 8x DIO DC 24V DO 1 A Diagnostic function
00028648	Front connector screw connection 392-1AJ00, 20-pin
00028647	Front connector screw connection 392-1AM00, 40-pin
SM 021 - Digital input, SLIO	021-1BF00 SLIO input module Type: SM 021 Version: 8 digital inputs, DC 24V
SM 022 - Digital Edition	022-1BF00 SM 022 - Digitale Ausgabe 8x DO DC 24 V 0,5 A
FM 050 - Counter module Eco	050-1BB30 FM 050 - Counter module Eco 2x counter 32 BFM 050 - Counter module Ecoit (AB), DC 24 V Up to 400 kHz
SM 031 - Analog input	031-1BD30 SM 031 - Analog input 4x AI 12 bits Voltage 0...10 V
SM 032 - Analog output	032-1BB40 SM 032 - Analog output 2x AO 12 bits Current 0(4)...20 mA Goods tariff number: 85389099
972-0DP10	EasyConn 90° - PROFIBUS connector Clock speeds up to 12 Mbit/s Metal case PG socket Switchable terminating resistor 90° cable outlet Bus diagnostics via LEDs
SM 221 - Digital input ECO	221-1BH30 16x DI DC 24 V

VIPA CPU 315SB	315-2AG23 VIPA CPU 315SB Type: 315SB, Powered by SPEED7 Device family: 300S+ Rated voltage: DC 20.4...28.8 V RAM: 1,024..4,096 kB onboard digital: -- DI/ -- DO/ -- DIO onboard analog: -- AI/ -- AO Interfaces... ..RJ45 (1x): Ethernet PG/OP communication ...RS485 (2x): MPI, PROFIBUS Slave, PtP: ASCII, STX/ETX, 3964(R), USS Master, Modbus Master/Slave ...SD/MMC slot: with locking expandable: - up to 32 modules can be connected in series programmable: - via WinPLC7, SIMATIC Manager and TIA Portal
SM 022 - Digital Output	022-1BF00 SM 022 - Digital output 8x DO DC 24 V 0.5 A
SM 032 - Analog output	032-1BB30 SM 032 - Analog output 2x AO 12 bit Voltage 0... 10 V
SM 322	Digital output 322-1BL00 SM 322 - Digital output 32x DO, in groups of 8 DC 24 V 1 A For 40 pole front connector Dimensions: 152 x 130 x 48 mm
972-0DP10	EasyConn 90° - PROFIBUS connector Clock rates up to 12 Mbit/s Metal housing PG socket Switchable terminating resistor 90° cable outlet Bus diagnostics via LEDs
972-0DP20	Clock rates up to 12 Mbit/s Metal housing PG socket Switchable terminating resistor 45° cable outlet Bus diagnostics via LEDs
972-0DP30	Clock rates up to 12 Mbit/s Metal housing Switchable terminating resistor 0° cable outlet Bus diagnostics via LEDs
IM 253DP - PROFIBUS-DP-Slave	253-1DP01 DC 24 V 12 Mbit/s Configuration via GSD file from VIPA Up to 32 modules (16 analog) 244 bytes input and 244 bytes output data
321-1BL00	SM 321 - Digital input 32x DI, two groups DC 24 V For 40 pole front connector
322-1BL00	SM 322 - Digital output 32x DO, in groups of 8 DC 24 V 1 A For 40 pole front connector
390-1AE80	Profile rail Length: 482 mm
390-1AJ30	Profile rail length: 830 mm
392-1AJ00	front connector screw connection 20-pin
392-1AM00	front connector screw connection 40-pin
214-1bc03	
Vipa053-1dp00	
215-2bm03	
214-2bt13	
215-2be03	
322-1bl00	

053-1dn00	
314-6cf23	* powered by SPEED7 * Memory [KB]: 512 - 2,048 * SPEED bus * Interface [RJ45]: Ethernet PG / OP communication * Interface [2x RS485]: MPI, PROFIBUS master / slave, PtP: ASCII, STX / ETX, 3964 (R), USS Master, Modbus Master / Slave * Onboard 8 DI / 8 DIO / 5 AI [current / voltage] / 2 AO / 1 Pt100 / 4 counter * incl. front connector * SD / MMC card slot with lock, up to 32 modules can be added, programmable via SPEED7 Studio, SIMATIC Manager and TIA Portal Successor of 314-6CF02
053-1mt00	
Vipa-Dea-Bg09	OUTPUT MODULE 64OUTPUTS 0.5AMP 150-250MA 24VDC
Yn000682	
215-1ba03	
214-2cm03	
Cp4-Bg62	PLC MODULE SIMATIC S5 1AMP 5-24V 8MBYTE RAM
Yn002729	
451-7la12	OUTPUT MODULE 32POINT DIGITAL
031-1bb60	
000-0ab00	
Dea-Bg04	32 IN/32 Out Digital I/O Module
Dea-Bg05	32 IN/32 Out Digital I/O Module
315-2ag12	CPU MODULE
201-1aa40	
Yn000640	
201-1aa10	
222-2bl10	
Vipa321-1bl00	
112-4bh02	
022-1bf00	SM 022 - digital output DO 8xDC 24V, 0.5A, incl. 001-0AA00 terminal module
201-1aa00	
Vipa331-7kf01	
114-6bj02	
Vipa222-1bf30	

Sm031-1bb90	
032-1cb70	
331-7kb01	
321-1bl00	
3221bl00	
3921am00	
Ssn-Bg89a	
Ssm-Md22005220	SSM-MD22 Communication Module PD1501
Vipa221-1bh30	
Yn001393	
Ssm-Md34d	Interface Sub Module
250-1bh10	
215-2bp03	
215-2bs33	
221-1bh20	
972-0dp01	
000-0dn00	
216-2ba02	
050-1bb40	
115-6bl32	CPU 115 MICRO PLC
253-1dp00	
214-2be03	
0211bf00	SM 021 Digital input DI 8xDC 24V, incl. 0010AA00 terminal module
214-2bs03	
040-1ca00	
031-1ca20	
313-5bf03	CPU MODULE
215-2bs03	
214-2bs13	
201-1aa20	

342-1ia70	COMMUNICATION PROCESSOR
032-1bb30	
032-1bb70	
610-3b4i1-Bxx	
222-1bf10	
Yn001758	
Cm201-1aa00	
115-6bl12	
214-1ba06	
Cp5-Bg71	PLC MODULE 5-24VDC 233MHZ PD4111
Vipa-7227	PC BOARD MODULE
032-1cb40	
214-Bc02	
Vipa332-5hd01	
Yn000689	
Vipa223-1bf00	
290-0aa10	
Vipa972-0d030	
221-1bh10	
053-1ip00	
031-1bb30	
214-1ba03	
317-2aj12	CPU MODULE 317SE SPEED-7 24VDC 2MB
290-0aa20	
900-2h611	
050-1ba00	
032-1cd40	
972-0dp20	
Vipa-313-6cf03	PLC MODULE CLASS C 64KB MEMORY 24VDC
	EasyConn PB 90 ° SubD connector 12MBit / s, metal housing, PGB socket, insulation displacement technology, switchable

972-0dp10	terminating resistor, 90 ° cable outlet, Bus diagnostics via LEDs
021-1bf00	SM 021 - digital input DI 8xDC 24V, incl. 001-0AA00 terminal module
Yn000655	
3921bm01	
Vipa007-1ab00	
232-1bd50	
Yn002739	
032-1cd30	
215-2bt13	
040-1ba00	
215-1ba06	
3211bl00	
Vipa 7722	Communication Submodule
Vipa201-1aa20	
231-1bd60	
290-0aa40	
953-1lm00	MCC, 4MBYTE SOR SPEED7 CPU
Vipa253-1dp01	
153-6pl80	
290-1af00	
Ssm-Bg43	INTERFACE BASIC MODULE FOR 3 PLUG-IN-MODULE
032-1bd30	
314-6cg13	
221-1bf00-Di	
Ssm-Bg81	Interface Module VIPA SSM-BG81
032-1bd40	
214-2bm03	
292-1af00	
322-1bh00	

053-1ec00	
221-1BF00	SM 221 - Digitale Eingabe 8x DI DC 24 V
050-1bs00	
207-1ba00	
032-1bd70	
032-1cb30	
3317kb01	
053-1pn00	
Ssn-Bg81l	Communications Module
000-0aa00	
Ssm-Bg41	INTERFACE MODULE BOARD
234-1bd50	
314-1sl01	CPU MODULE 314
214-2bs33	
3146cg13	
Sw900h0la	
Vipa-Ssm-Bg41	MODULE COMMUNICATIONS PROCESSOR BASIC
3146cg23	UNIT
232-1bd30	
900-2h681	ROUTER VPN
214-2bp03	
Ssm-Bg43d	INTERFACE MODULE BOARD
000-0ac00	
250-1bs00	
153-6pl10	
972-Odp01	
214-1ba02	
032-1cd70	
050-1bb00	
Vipa201-1aa10	
215-1ba05	CPU215PLC CPU 128KB WORK MEMORY 192KB LOAD MEMORY

151-4ph00	
62f-Fee0-Cb	OPERATOR INTERFACE 5.7INCH TOUCHSCREEN TP 605CQ
215-2cm03	
Vipa332-5hb01	
3921aj00	
Vipa-Dea-Bg09v11	OUTPUT MODULE 64OUTPUTS 0.5AMP 150-250MA 24VDC
215-1ba02	PLC CPU DC 24V MMC SLOT RTC
215-2bs13	
Vipa312-5be13	
221-1BF30	SM 221 - Digital input ECO 8x TUE DC 24V Goods tariff number: 85389099
972-Odp10	
342-1ca70	CANOPEN MASTER SPPED BUS MODULE
290-0aa80	
Yn002732	
114-6bj03	
214-2bm06	
953-0kx10	
953-1ll00	MEMORY CARD MMC 2MB
314-6cf02	CPU MODULE STEP7 PROGRAMMABLE
231-1bd52	
315-4ne12	CPU
Dea-Bg09	OUTPUT MODULE 64OUTPUTS 0.5AMP 150-250MA 24VDC
050-1ba10	
032-1bb40	
Vipa-7642	INTERFACE MODULE
050-1bb30	
290-1af30	
313-5bf13	
Vipa-Ssm-Bg42	INTERFACE BASIC MODULE FOR 2 PLUG-IN-MODULE

[153-6pl00](#)

[214-1bc06](#)

[053-1ca00](#)