

Visolux



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Visolux** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Visolux Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

| rn | Aıklama |
|--|--|
| 181 574 | sensor amplifier and optical part |
| J887406 | |
| Visolux | |
| 419204 | |
| 1057520062 | |
| RL 12.1 24V | G2.110.1461/01 |
| 418082 | |
| ML-4-T-GA | |
| RIk 28-55-31-116 | |
| RIk248h9.664000 | |
| 409615 | |
| RIk28-8-H-2000-Ir-Z/31/116 | Reflection light sensor HGA Touch range: 20 ... 2000 mm Light emitter: IRED Type of light: infrared, alternating light, 880 nm Signal output: relay, 1 changeover contact Switching type: light / dark switching, switchable (thereby is the one H / D switch only in function, if the other one in the position "dark switching" is.) Connection: terminal compartment with 8 spring terminals for Core cross section 0.5 ... 1.5 mm ² , stripping 7.5 ... 8.5 mm, cable gland M16x1.5 Operating voltage: 12 ... 240 V AC / DC Ambient temperature: -40 ... 60 ° C (-40 ... 140 ° F) Country of origin: Vietnam Customs Tariff No.:8536 5080 |
| Ls230-Da-Rt/F3-F5 | PHOTOELECTRIC SENSOR HEAD 24VDC |

| | |
|--|---|
| Sla40 | |
| 418317 | Single Path light Beam Switch M15 |
| Photocell MI4.2-8-H-40-Ir-2449 Tw=13-40mm, Vga-Hg | |
| M24-765576 | |
| 9015003sl20-E | |
| 9015004sla20-S | |
| 9015002sl20-S | |
| L22-Lk22-1997-47oz382981 | |
| Su10-2446 | |
| SI30-1351-E | |
| Ltk-6000 | PHOTOELECTRIC DOOR/GATE/ELEVATOR 12-24VAC |
| Lt2000-2k-1937 | MODEL:LT2000-2K-1937 |
| Slva-4kplus | SAFETY CONTROL UNIT 115VAC |
| 9409044 | |
| RI24-8-200/49/76a/116419233 | |
| MI48h | |
| Fibre Optics Lle 04-1,6-0,4 Wc3 Nr.: 4.857.01 L=40cm | |
| Ls600-Da-Ibs/F2 | PHOTOELECTRIC OPTICAL DATA COUPLER 250M RANGE |
| 418628 | PHOTO AUTOMATION INSTRUMENTS-(LS230-DA-GUF) |
| 418319 | Single Path light Beam Switch MV15/47 |
| 414109 | |
| Faseroptik Llr 04-1,6-0,5 Qw1x4 Nr.: 4.815.01 L = 50cm | |
| Ls230-Da-Rt/F5-F3 | PHOTOELECTRIC SENSOR HEAD 24VDC |
| 9.247013 | |
| Edm120-2300 | DISTANCE MEASURE 24VDC 0.5-120M |
| 418603 | PHOTOELECTRIC LK24 12/240V AC/DC |
| 1396030004 - Su 11-2158/33 | |
| Dad-8/8 | PHOTOELECTRIC SYSTEM 10-60VDC |
| Reflector Vr10 Order No.: 113950 | |

| | |
|--|---------------------------------------|
| 9425000 | |
| Ls500dap | |
| RI206 | |
| 103033 | |
| 9.537 020 TI 25-8 | |
| Ls230-Da | |
| Reflex-Lichtscanner Mlv40-8-H-1463 10-30v Dc, Rw = 1-8cm | |
| RI9-8-W-16-25-1200 | |
| 418576 | PHOTOELECTRIC (AUTOMATION) |
| Fotzellenverstärker Mlv40-LI-Ir-2492 Best.Nr .: 9.705078 | |
| Ls 500-Da-P-2350/F2 | Photoelectric Sensor Module 9.259.029 |
| 9825035slv-2k | |
| Reflex-Lichtscanner MI4.1-8-H-2486 55-58mm | |
| Edm9-120-Ibs | PHOTOELECTRIC DISTANCE MEASURING |
| 421021(Ex. 419773) | |
| Reflex-Lichtschranke Mlv40-54-G-1700 10-30v Dc,Rw=0-20cm, Vr10 | |
| Emitter/Receiver Photocell MI5-T-M-1628 - 10-30v Dc, Rw= 0-50cm | |
| Faseroptik Llr 04-1,6-0,5 Wc3 Nr .: 4.813.10 L = 50cm | |
| 9472020 | |
| 9015005sla20-E | |
| Reflex Lichtscanner MI4-8-H-M-1348 10-30v Dc, Rw = 1-2cm, 55cm | |
| Dn80 | |
| 9825055slva-4k | |
| Lle4-80505 | |
| Fiberoptik Lle 04-1.1-0.55 Gk6 Best.Nr .: 4.940 01 L = 0.55m | |
| Lk28-Z-F1/31/116 | |

| |
|---|
| Ftk1550000 |
| RI32-8-H-Rt |
| SI20 |
| 1452270181 Obsolete Sensor |
| Mlv40-8-H2209 |
| 409617 |
| Sla20 |
| Photocell MI4.1-54-F/40b/95/110 Order No.: 418738 |
| Fibre Optics Llr 04-1,6-0,5 Qw1x4 Quer Nr.: 4.913.01 L=50cm |
| RIk23-8-H-100-Ir/31/116 - Fotosel |
| RIk20-54-1586 |
| Reflexbeleuchtung Mlv40-54-1371 10- 30v Dc, Rw = 0,1-0,6m, Vr10 |
| MI48ksu3347 |
| 9546000 |