

Vivoil

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Vivoil Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Vivoil T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
9RD0229	RV-1D / 4.9x2 p max: 220bar - input 1x1 / 2 "IG 2-way gear flow divider without valves - guidelines for the design and commissioning of flow dividers be sure to note on our homepage! Weight: 3.2800 kg / 3.2800 kg Item number: 84122981 Country of origin: IT
1964.565.X071	H80 11cc Bidirectional Steering
1964.509.X071	H65 11cc Bidirectional Steering
XV2+2P/11+11S-LK30/30-30/30	Z024-00110-9999 9M201ECA4747 2-way aluminum pump - counterclockwise - EL = 197mm 2-way external gear pump with aluminum body Direction of rotation: counterclockwise Sealing material: NBR 1st stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Mounting flange: Fitting Ø 36.5 mm - 4-hole fastening 96.2 mm x 71.5 mm Drive shaft: conical 1: 8 - woodruff key 4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 2nd stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 For applications in which multiple pumps are supplied from separate tanks, please

	<p>stop first consultation with our technical department. Weight: 5.1441 kg / 5.1441 kg Item number: 84136031 Country of origin: IT</p>
XV2+2P/11+4S-Ø36,5-CO.001-LK30/30-30/30 Euro	<p>2-way pump - counterclockwise - EL = 182 mm 2-way external gear pump with aluminum body and aluminum flanges Direction of rotation: counterclockwise Sealing material: NBR 1st stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Mounting flange: Fitting Ø 36.5 mm - 4-hole fastening 96.2 mm x 71.5 mm Drive shaft: conical 1: 8 - woodruff key 4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 2nd stage: External gear pump size 2 Delivery volume: 4.2 ccm / rev Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1</p>
Z024-00110-99999	<p>9M201ECA4747 XV2 + 2P / 11 + 11S-LK30 / 30-30 / 30 2-way aluminum pump - counterclockwise - EL = 197mm 2-way external gear pump with aluminum body Direction of rotation: counterclockwise Sealing material: NBR 1st stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Mounting flange: Fitting Ø 36.5 mm - 4-hole fastening 96.2 mm x 71.5 mm Drive shaft: conical 1: 8 - woodruff key 4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 2nd stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1</p>
022-080-01000	<p>X2F4102QOOA XV2F/4D-Ø36.5-SCF.01-30/30 4.2ccm/rev - clockwise - 260 bar End section external gear pump size 2 with aluminum body and aluminum flanges Delivery volume: 4.2 ccm/rev Direction of rotation: clockwise Mounting flange for the pump installed in front of it, size 2: fitting Ø 36.5 mm - 4 hole fastening 96.2 mm x 71.5mm Drive shaft: splined 9 teeth DIN5482 - 17x14 - Ø 16.5 h11 Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 Installation length: 87.2 mm Seal material: NBR Permissible shaft torque: 86.2 Nm Continuous pressure limited by drive shaft: 260 bar Continuous pressure: 260 bar Peak pressure (max. 0.5 sec): 300 bar Minimum speed: 700 rpm Maximum speed: 3500 rpm</p>
022-060-01000	<p>X2T4102E00A XV2T/4D-Ø36.5-COP.01-30/30 4.2ccm/rev - clockwise - 260 bar Front section external gear pump size 2 with aluminum body and aluminum flanges Delivery volume: 4.2 ccm/rev Direction of rotation: clockwise Mounting flange: Fitting Ø 36.5 mm - 4 hole mounting 96.2 mm x 71.5 mm Mounting flange for the middle or end section size 2: fitting Ø 36.5 mm - 4 hole fastening 96.2 mm x 71.5mm Drive shaft: conical 1:8 - disc spring 4 mm - through drive geared 9 teeth DIN5482 - 17x14 - Ø 16.5 h11 Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 Installation length: 83.4 mm Seal material: NBR Permissible shaft torque: 86.2 Nm Continuous pressure limited by drive shaft: 260 bar Continuous pressure: 260 bar Peak pressure (max. 0.5 sec): 300 bar Minimum speed: 700 rpm Maximum speed: 3500 rpm</p>
026-001-1200	<p>8KITR004 Connection kit XV 2+2 without flange - NBR</p>

X3P7802AEEA	014-040-01500 XV3P/38D-Ø50.8-COP.001-1-1 38.47ccm/rev - clockwise - 250bar External gear pump size 3 with aluminum body and aluminum covers Discharge volume: 38.47 ccm/rev Direction of rotation: clockwise Mounting flange: fitting Ø 50.8 mm - 4 hole fastening 128.1 mm x 98.4 mm - Ø 11 mm Drive shaft: conical 1:8 - disc spring 4 mm Suction connection: G 1" Pressure connection: G 1" Installation length: 143 mm Sealing material: NBR Permissible shaft torque: 482 Nm Continuous pressure limited by drive shaft: 250 bar Continuous pressure: 250 bar Peak pressure (max. 0.5 sec.): 270 bar Minimum speed: 700 rpm Maximum speed: 2800 rpm
13 4e2	
9rd0427	
X2p4702e00a	
X2p4702ecba	
7p2302001	
X2p4502e00n	
Rd9m100es	
X0p0502abba	
Rd15m100es	
X1p2902fbba	
9s202aga0101	
9rv03a34	
X0r1321bbbe	
Rv-2v/17x2 Eav 70-210bar	
9rd0429	
X2p6352iqpa-40cc	
Xv2p-D-1/2-1/2	
7p3402005	
7p2502005	
Kv-2dfv/40x2	
X1p-2502fbba	
X2p5702eqpa	
9rv04a27	

[Mtz-2-2-17-G](#)

[Rv-1s 9rs 03d36](#)

[X1p2302fjja](#)