

Vivolo

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Vivolo Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Vivolo T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
XV1P/1,2DC	9S202ECA4343 XV2+2P/6+6D-Ø36.5-CO.001-LK30/30-30/30 euro-DS 9S202ECA4343 double pump EL=178mm 2-way external gear pump with aluminum body and aluminum flanges/screw-through design Direction of rotation: clockwise Seal material: NBR 1st stage: External gear pump size 2 Delivery volume: 6.00 ccm/rev Mounting flange: fitting Ø 36.5 mm - 4 hole attachment 96.2 mm x 71.5 mm - Ø 9 mm Drive shaft: conical 1:8 - Woodruff key 4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 2nd stage: External gear pump size 2 Delivery volume: 6.00 ccm/rev Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1
Z024-01271-99999	
Z024-01271-99999-U	9S202ECA4343 XV2+2P/6+6D-Ø36.5-CO.001-LK30/30-30/30 euro-DS 9S202ECA4343 double pump EL=178mm 2-way external gear pump with aluminum body and aluminum flanges/screw-through design Direction of rotation: clockwise Seal material: NBR 1st stage: External gear pump size 2 Delivery volume: 6.00 ccm/rev Mounting flange: fitting Ø 36.5 mm - 4 hole attachment 96.2 mm x 71.5 mm - Ø 9 mm Drive

	<p>shaft: conical 1:8 - Woodruff key 4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 2nd stage: External gear pump size 2 Delivery volume: 6.00 ccm/rev Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1</p>
010-240-01000	<p>X2P4102E00A XV2P/4D-30/30 4.2ccm/rev - clockwise rotation - 260bar External gear pump size 2 with aluminum body and aluminum flanges Delivery volume: 4.2 ccm/rev Direction of rotation: clockwise Mounting flange: fitting Ø 36.5 mm - 4 hole attachment 96.2 mm x 71.5 mm - Ø 9 mm Drive shaft: conical 1:8 - Woodruff key 4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 Installation length: 87.2 mm Seal material: NBR Permissible shaft torque: 233.2 Nm Continuous pressure limited by drive shaft: 260 bar Continuous pressure: 260 bar Peak pressure (max. 0.5 sec): 300 bar Minimum speed: 700 rpm Maximum speed: 3500 rpm</p>
021-010-08450	<p>9RS03D25 RV-1S/3,8x3 EAV 70-210 bar p max: 220bar - Entrance 1x1/2" IG</p>
Z024-02078-99999	<p>9M202FGA2101 XV1+0P/2.6+0.17D-3/8-3/8-1/4-1/4 2-fold aluminum pump - clockwise - EL=158mm 2-fold external gear pump with aluminum body and aluminum flanges Direction of rotation: clockwise Seal material: NBR 1st stage: External gear pump size 1 Delivery volume: 2.60 ccm/rev Mounting flange: Fitting Ø 25.4 mm - 4 hole mounting 71.9 mm x 52.4 mm - Ø 7.15 mm Drive shaft: conical 1:8 - disc spring 2.4 mm Suction connection: IT 3/8" Pressure connection: IT 3/8" 2nd stage: External gear pump size 0.5 Delivery volume: 0.16 ccm/rev Suction connection: IT 1/4" Pressure connection: IT 1/4"</p>
016-120-01300	<p>X2M5301EPPE XV2M/19-Ø36.5-CO.001-40/40 external leakage oil 19.2ccm/rev - reversing - 210bar External gear motor size 2 with aluminum body and aluminum covers Delivery volume: 19.2 ccm/rev Direction of rotation: reversing Drainage: external Mounting flange: Fitting Ø 36.5 mm - 4 hole mounting 96.2 mm x 71.5 mm - Ø 9 mm Drive shaft: conical 1:8 - disc spring 4 mm Oil connections (IN/OUT): 2x LK 40 mm - M8 x 1.25 Leakage oil connection: G 1/4" Installation length: 112.2 mm Seal material: NBR Permissible shaft torque: 233.2 Nm Continuous pressure limited by drive shaft: 210 bar Continuous pressure: 210 bar Peak pressure (max. 0.5 sec): 250 bar Minimum speed: 700 rpm Maximum speed: 3000 rpm</p>
010-240-01400	<p>X2P4902EPOA XV2P/14D-Ø36.5-CO.001-40/30 14.4ccm/rev - clockwise - 250bar External gear pump size 2 with aluminum body and aluminum flanges Delivery volume: 14.4 ccm/rev Direction of rotation: clockwise Mounting flange: Fitting Ø 36.5 mm - 4 hole mounting 96.2 mm x 71.5 mm - Ø 9 mm Drive shaft: conical 1:8 - disc spring 4 mm Suction connection: LK 40 mm - M8 x 1.25 Pressure connection: LK 30 mm - M6 x 1 Installation length: 104.2 mm Seal material: NBR Permissible shaft torque: 233.2 Nm Continuous pressure limited by drive shaft: 250 bar Continuous pressure: 250 bar Peak pressure (max. 0.5 sec): 290 bar Minimum speed: 700</p>

	rpm Maximum speed: 3500 rpm
010-240-01500	X2P5102EPOA XV2P/17D-Ø36.5-CO.001-40/30 16.8ccm/rev - clockwise - 230bar External gear pump size 2 with aluminum body and aluminum flanges Delivery volume: 16.8 ccm/rev Direction of rotation: clockwise Mounting flange: Fitting Ø 36.5 mm - 4 hole mounting 96.2 mm x 71.5 mm - Ø 9 mm Drive shaft: conical 1:8 - disc spring 4 mm Suction connection: LK 40 mm - M8 x 1.25 Pressure connection: LK 30 mm - M6 x 1 Installation length: 108.2 mm Seal material: NBR Permissible shaft torque: 233.2 Nm Continuous pressure limited by drive shaft: 230 bar Continuous pressure: 230 bar Peak pressure (max. 0.5 sec): 270 bar Minimum speed: 700 rpm Maximum speed: 3500 rpm
021-010-04500	9RS02C23 RV-1S/3.2x2 EAV 10-105 bar p max: 220bar - input 1x1/2" IG 2-way gear flow divider with central end position compensation valve -
9M202FGA2101	
010-050-01600	X1P2502FIIA XV1P/3.8D-Ø25.4-CO.001-30/30 3.64ccm/rev - clockwise - 250bar External gear pump size 1 with aluminum body and aluminum covers Displacement: 3.64 cc/rev Direction of rotation: clockwise Mounting flange: fitting Ø 25.4 mm - 4 hole mounting 71.9 mm x 52.4 mm - Ø 7.15 mm Drive shaft: conical 1:8 - disc spring 2.4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 Installation length: 88.5 mm Sealing material: NBR Permissible shaft torque: 43 Nm Continuous pressure limited by drive shaft: 250 bar continuous pressure: 250 bar Peak pressure (max. 0.5 sec.): 300 bar Minimum speed: 700 rpm Maximum speed: 6000 rpm
028-010-02600 Dichtsatz	
X2p4902ecba Gear Pump Xv-2p/14 Cm3/Rev	
X1u2561bbba Hydraulikmotor Unidirectional Hydraulic Motor	
X2p4302ebba Pump Vivolo Xv-2p/06	
Double Pump Xv2p/19+ Xv1p/1,7 9m202ega5318	
9rs-03-E-03	
Xv 1p-S/A	
X0p0601adda Gear Pump Xv/0p/0.76cm3/Rev	
022-030-01700 / X1t2702fiia 022-Zahnrad-Pumpenstufen Xv (Frontstufe)	
X1p2501fjja Pump Xv-1p/3,8 Cm3/Rev	
Hydraulikmotor Typ Sae Aa Series Xv	

Vivolo X1u2561ebba
022-052-01900
X2p5302ecba Gear Pump Xv-2p/19 Cm3/Rev
X2p4302ebba Pump
010-050-02150 / X1p3401fiia
X0p0602abba Gear Pump Xv/0p/0.76cm3/Rev
X2t4302e00a Pump Xv2-T 6,00
Xip2002fzbb Pumpe
Xv-2p
X1p3443dzzb
9m322fqa494745 Triple Pump Xv2p/14+11+9
010-050-01700 / X1p2702fiia 010- Zahnrad-Pumpen Xv
010-060-02200
X0p0702abba
X3p7432beea Gear Pump Xv-3p/32 Cm3/Rev
X2p4702ebba Gear Pump Xv-2p/11 Cm3/Rev
Xv 2p/D/C 22
010-050-01600 / X1p2502fiia 010- Zahnrad-Pumpen Xv
X2m5519crrf Hydraulic Motorxv-2m/22
X3p7402abba Pumpe Gear Pump Xv- 3p/32 Cm3/Rev X3p7402abba
9rd0527 Flow Divider Rv-1d 4,3x5
X0p0402abba Pump
9rd 02 51 Flow Divider Rv-2d 17x2
Hydraulikmotor Typ Sae Aa Series Xv Vivolo X1u2561bbba
010-050-02200 X1p3602fiia
062-040-02100 Axko Konstantpumpe 130ccm-Reversierbar - 64,5

8kgx3p1.V Pads Set
X3p7432beea Gear Pumpxv-3p/32 Cm3
X1p2102fbba Gear Pump Xv-1p/2.6 Cm3/Rev
028-010-02500 8kgx2m1.A Dichtsatz- Xv2-M/U (Nbr) Ø36,5-Ø50-Ø80-Ø82,5 Zahnrad-Motor Xv2u+m-Ø36,5+50+80
000022157
6295754 Pumpe X3p7202aaaa
022-050-01600 / X1f2572tiia 022- Zahnrad-Pumpenstufen Xv (Entstufe)
X3p7202aaaa Hydraulikpumpe
9d 03 89 Mengenteiler Der Xv-2d
X1p1602fbba Pump
9d0274 Flow Divider
014-040-01964
010-240-01400 / X2p4902epoa 010- Zahnrad-Pumpen Xv
9d0389
X2m4501ebbf Hydraulic Motor Xv-2m/09
Xv 1p- S/A
X1p2702fiia
X1p3143lzzb
9d0289
X2p5152icba Gear Pump Xv-2p/17 Cc/Rev
010-060-01200
X1m2301fbb2 Hydraulische Pumpe
9d 02 89 Mengenteiler Der Xv-3d
Xv-0p-D
X1u2561ebba Hydraulikmotorunidirectional Hydraulic Motor
Gear Pump Xv/0p/0.45cm3/Rev

X0p0402abbaxv0p/0.45 - O22 /D - Ci001
- 1/4" Bsp - 1/4" Bsp
X2p5502ecba Pump 150bar Clockwise Rotation
9rd 02 51 Flow Divider
028-010-02400 8kgx2p1.A Dichtsatz-Xv2p-Komplett-Nbr Zahnrad-Pumpe Xv2p-Ø36,5+50+80+82,5
X2t4102ebba Pump Xv2-T 4,00
9rd 02 47 Mengenteiler Der Rv-2d
X3p8332iffa
X0r1324bzze Reversible Pump Xv-0r/2,3
X1p3402fbba
X1m2301fbbe Gear Motor Xv-1m/3,2
X2p4502ebba Gear Pump Xv-2p/09 Cm3/Rev
X1p2702fbba
9rs05c27 Flow Divider Rv-1s/4,3x5
X2?4732?Sra Pumpe
9rs-03-D-02
Xv1p/5