

Vmeca



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Vmeca Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Vmeca T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

| ¼r¼n | Aıklama |
|--|--|
| Vc202p | vacuum injector Mini Cartridge "VC202 Series" with stopper Max. Vacuum (-kPa): 90 Max. Suction power (NI / m): 41 Compressed air consumption (NI / m): 17 ~ 32 Working temperature: -20 ° C ~ 80 ° C |
| VBF25PU-14F | Flat bellows suction cups with 1 1/2 folds Ø 25 mm Material = polyurethane (PU) Color = orange Fitting = 1/4 "female |
| L1815 Compensators | |
| VBU55 Vakum Ped | |
| 01.T.03.001 | |
| 01.T.03.001.164919 | |
| 129227 | |
| FCF70-BJ03-PU-L30S-18F | |
| FCF70-BJ-PUL30S- 18F | |
| GM130X600-L4 | |
| L515T | |
| MC20BX-N2B40FP48W 3D(FDA) | |
| MC20BX-N2B40F-P48W 5D | |

| | |
|---------------------------------|--|
| MC25CP- N1B40F | |
| P48-WS5 | |
| VB17 | |
| VC202 | |
| VD50N-18F | |
| VDF100-PU-18F | |
| VF20N | |
| Vmeca 3032 | |
| Vou 15x45 | |
| VTC3031-2 | |
| VTC3032-2 | |
| VTC3134-2 | |
| VTFE341 | |
| VTFE40 | |
| VTM10-B | |
| VTM30-B | |
| VU20-S | |
| VU50S-14M | |
| VTX30-B | Mini Pump "X-series" Max Vacuum (-kPa): 92 Max. suction power (NI/m): 185 Compressed air consumption (NI/m): 129.6 ~ 144 Noise Level (dBA): 60~68 Working Temperature: -20°C~80°C Air connection: A G 1/8" Vacuum connection: V 3/8" Country of origin: Korea Customs Tariff No.: 84141089 |
| G80X150-MC2-ES | V-GRIP System Dimensions = 80mm X 150mm foam (EPDM), round suction openings Max. Vacuum (-kPa): 75 Max. suction power (NI/m): 724 Air consumption (NI/m): 208 MC2 = 2X two-stage ejector ES = standard, fixed check valve close distance |
| VTF38-IN | In line vacuum filter G 3/8" connection |
| VFC75PU-1 838MF | Flat suction cups curved Ø 75 mm Material = Polyurethane (PU) Color = orange Fitting = 1/8" male Fitting = 3/8" female |
| VFC60PU-1 838MF | Flat suction cups curved diameter 60 mm Material = Polyurethane (PU) Color = orange Fitting = 1/8" male Fitting = 3/8" female Country of origin: Korea Customs Tariff No.: 401699 |
| | Turtle Pump "Midi VTC Series" 1X three-stage ejector with suction valve, blow-off valve integrated filter(PE) and double |

| | |
|---|--|
| VTC3031-2 | silencer Max Vacuum (-kPa): 92 Max. suction power (NI/m): 341 Compressed air consumption (NI/m): 97 ~ 152 Noise Level (dBA): 50~60 Working Temperature: -20°C~80°C |
| VF110N-12F | flat suction cup Ø 110 mm Material = Nitrile (NBR) Color = Black Aluminum fitting = 1/2" female without a mesh filter |
| vbf25p(0) | |
| GMT VAKUM VALF ; VMS14M-3-3 ; V-MEGA | |
| VALF ; GMT VAKUM VALF ; MS18M-3-3 ; V-MEGA | |
| GMT VAKUM FİLTR VTFE502 V-MEGA | |
| 20 414803 | |
| Vms 18d-3 Vacuum Release Valve (Electrovalve) | |
| Vq203s-38f-S-A3 | |
| Vf110n Flachsauger | |
| L1230 | |
| G130x220-L4-BI15s | |
| 20 600901 | |
| Vs100-E-12f | |
| Vtfe342 | |
| Vdf40xx | |
| G16x60-C202-B | |
| Vms 38-3 Vms 38 Control Valves | |
| G80x150-Mc2-Es | V-GRIP System V-Grip System, 2-Cartridge, 80 x 150 mm Standard, Fixed Check valve, Narrow Spacing customs tarif: 84141089 country of origin: Korea |
| Vtfe501 | |
| G130x600-L8-Es | |
| L1250t | |
| U45-S3 | |
| Vb 10 Vacuum Pump | |
| Vtf38-1 | |
| Vkm74-S1-W33-G | |
| | |

| |
|---|
| Vcx74-S1-A33-8 |
| Vms14-M-As |
| 20 600901 Smart Cup |
| Vms 18d-3 |
| Vtc3134-2-Asv-A3r3-DI-Sg3-V |
| Kps-2s Sauger Grosse Å216;28 Material = Sil |
| Vms14d-3-1 |
| G80x200-Mc2-Es |
| Vc303s-N |
| Vtm25-1434-A |
| Vtrf 15-3-Al |
| Vtffx-96 Filter Cover / 13c301 |
| Vtfe27.5-39096 |
| Stopper A For B2.5/20 Series And X Type Sealing Lip |
| B2.5/20-U25-S-B-18m |
| Vc303p |
| Vbl20n |
| Vtf01-118 |
| Art. Nr. Vtf12-96 |
| Stopper B 40 |
| 20 104810 |
| Vbf25pu-18f Flach-Balgsauger Mit 1 1/2 Falten |
| Vbl40n |
| Nf 40-12-9p-18f |
| Vs100e |
| Vb 10 |
| U25 |
| Vf110n |
| Vtf38-In |

| |
|---|
| Vts10 |
| Vtf34-1 |
| Kps-3s |
| Vtc3134-2-A3r3-Sg2p |
| Ms 20 B |
| Vb40n |
| Kps-2s Sauger Grosse Ø28 Material = Sil |
| U30-S |
| Vtfe 502 |
| Vtm50l-1434-A |
| B1.5/20 |
| Bs 245 01.T.03.004.152426 |
| Vtg ? 18 |
| Vtc3032-2-A3r3-CI-Sg2 |
| Vbx55-Pu-14m |
| 01.T.03.002. 108707 |
| 3500031103 |
| Wf12a |
| Vms18-3-1 |
| Vsmr203-F |
| U45-S5 |
| Vb50-Pu-14m-Ev |
| Vms18d-3-1 |
| L1250t Ausgleichhalter |
| Vbf25pu-18f |
| 20 102000 |
| Vtx5-C-V |
| Stopper D 20series |
| Vms 38-3 |
| Vtc 3031-2-As |

[Vtfe47.4-62118](#)

[20 104820](#)

[Vtf12-96](#)