

## Vortex

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Vortex** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Vortex T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">106BSP-8-H</a>	
<a href="#">20025 Inox</a>	
<a href="#">2700000150</a>	
<a href="#">2710127025</a>	
<a href="#">2710200213</a>	
<a href="#">35H</a>	
<a href="#">620-1BSP</a>	
<a href="#">721BSP-25H, 1500BTUH</a>	
<a href="#">BP2612</a>	
<a href="#">BX17X1700 LI</a>	
<a href="#">DVC5X7-MG</a>	
<a href="#">EXAIR 4040 2800BTU</a>	

<a href="#">GS06 -15</a>	
<a href="#">GS08 -15</a>	
<a href="#">GS10 -15</a>	
<a href="#">Laufrad VXC 10/45-N</a>	
<a href="#">PL20C-6AIS</a>	
<a href="#">TOP-YTH1500A2-T216EVD20CF</a>	
<a href="#">Tube 308BSP-35H (BP3240)</a>	
<a href="#">VXC 10/45-N</a>	
<a href="#">AS007 - Vortex Flow Sensor</a>	G3/4A - 1,8...32 l/min - analog 4...20 mA
<a href="#">Mechanical Seal (Belonging to Vortex 9 Stage)</a>	Booster) RT-240 in Marked Dimensions as in the Attached Picture
<a href="#">SOLVAHT 220 VAC 5.0 VA MODEL : VC-B2</a>	
<a href="#">CABINET BP4030 // CABINET COOLER BP4030</a>	
<a href="#">VX150 DRAIN PUMP</a>	
<a href="#">GRA350-F-AP-S4-MG-PET</a>	Vortex Model No. GRA350-F-AP-S4-MG-PET, 350MM Quantum Series Orifice Gate Valve. Aluminum valve body with live loaded, wear compensating seals, a 304 stainless steel blade, main flange and orifice liners. Material contact is 304 stainless steel and polymer. ıOversized double acting air cylinder actuator ı(AP) - Inlet and Outlet Flanges match #125/150 ANSI mounting pattern. Flanges are aluminum to prevent corrosion due to oxidation and have blind tapped steel thread inserts for bolted customer connection. Caution: Using a bolt longer than the specified maximum will result in damage to the gate valve. Consult IOM manual for correct bolt length. ı(MG) - Air cylinder is equipped with a magnopiston for use with magnetic reed position indication switches. ı(PET) - Valve is rated for 180F(82C) maximum continuous service. PET pressure plates are backed with a foam void filler and live loaded natural rubber load seals. ıValve has boss welded into main body to accept proximity switches. **OPTIONAL ACCESSORIES**
<a href="#">GRFISS-14</a>	14" Special Service Inlet, 304 stainless steel construction, eliminates material packing and reduces wear on seals; should be used when closing on abrasive, potentially sticky, pelletized, or granular materials, (adds 3/16" to OAH of valve). NOTE: RECOMMENDED WHEN VALVE IS INSTALLED IN HORIZONTAL PLANE. NOT RECOMMENDED WHEN VALVE IS TO BE INSTALLED VERTICALLY.
<a href="#">2F375-24ES1-24VDC</a>	Air Control Assembly, single solenoid, 24v DC/1.5 W, IP 65, G 3/8 ports, flow rate 3200 l/min, includes Polyurethane tubing, fittings and mounting brackets.

<a href="#">2CC1A-SPST</a>	Magnetic Reed Switch, SPST, Normally Open, NEMA 6 IP67, CSA Approved, 5-240 Volts VDC/VAC 50/60Hz, 2 wire output, 30 W/1 AMP Max, LED indication light, 9 foot PVC cable. CAUTION: Do not exceed rated wattage/current, permanent damage to sensor may occur.
<a href="#">Tube</a>	
<a href="#">FA08-M6-HT3-P-X</a>	SLIDE GATE VALVE
<a href="#">5890 SST300 - AFYON STEAM TURBINE MAIN STEAM LINE</a>	16 BAR 360 ¼C 60 t/h DN300 PN40
<a href="#">5897 SST600-SAMSUN STEAM TURBINE MAIN STEAM LINE</a>	6 BAR 360 ¼C 42 t/h DN500 PN16
<a href="#">EFOR BOILERS SUPERHEATER LINE</a>	16 BAR 360 ¼C 4.6 t/h DN100 PN40
<a href="#">BOILER-2 FIELD STEAM COLLECTOR MAIN STEAM LINE</a>	16 BAR 360 ¼C 27 t/h DN250 PN40
<a href="#">MRC10</a>	
<a href="#">Air Knife For Archimedes Pat. 2009 097 22</a>	
<a href="#">Pmb-4-Ut</a>	
<a href="#">Gvp 01</a>	
<a href="#">Cold Air Gun 620-1bsp</a>	
<a href="#">83f-Tihs2dttje-N</a>	
<a href="#">Exair 4040 2800btu</a>	
<a href="#">60040a-Nema Type 12</a>	
<a href="#">Gc-6sb</a>	
<a href="#">Ef73-Dn50 Pn40</a>	
<a href="#">Archimedes Pat. 2009 097 22</a>	
<a href="#">Vg-T2 400-00</a>	
<a href="#">4m25a-24es1-24vdc</a>	
<a href="#">4cc1a-Spst</a>	
<a href="#">H2o Guardian</a>	
<a href="#">Vv-Vt-Bf-6-300-Hdi</a>	
<a href="#">A-70325-220v</a>	
<a href="#">Dn200</a>	
<a href="#">Tube For Archimedes Pat. 2009 097 22</a>	

<a href="#">Dn16-Dn32</a>	
<a href="#">308mh</a>	
<a href="#">Type 20e-300model .P/N: PI20c-6ais. Size: 2ã39;Ã39; X 300ã Obsolete, No Replacement</a>	
<a href="#">Cold Air Gun 630-1bsp</a>	
<a href="#">Ef73-Dn80 Pn40</a>	
<a href="#">83f-A02s1sstna</a>	
<a href="#">Vm 0070 10 02</a>	
<a href="#">Gc-2ss</a>	
<a href="#">Gc-2ss-M4 260.00</a>	
<a href="#">Vor.760</a>	COOLER SYSTEM MINI 8SCFM
<a href="#">106bsp-8h</a>	
<a href="#">Bw 152 Ot Obsolete,Repleced By Bwo 155 R</a>	
<a href="#">610-1bsp</a>	
<a href="#">610-26+701s-24a</a>	
<a href="#">Sa225tv1-Ws1</a>	
<a href="#">308bsp-35h</a>	
<a href="#">Vg-T2</a>	
<a href="#">Abb Trio-Wirl Vr 42 Order No: 240069595/X019 Qmax Dn: 1900.0 M3/H,Mat: 1.4571/1.4571/1.4571 Gasket:</a>	
<a href="#">Vt-Bf-4-300-M1</a>	
<a href="#">W4000-15g-W-F1 Ckd</a>	
<a href="#">106-2-H</a>	
<a href="#">7725</a>	ENCLOSURE COOLING SYSTEM TYPE 4/4X
<a href="#">Gc-6sb-M4 768.00</a>	
<a href="#">7735</a>	ENCLOSURE COOLING SYSTEM 4/4X 2500BTUH 35SCFM
<a href="#">Dy150-Dbmba1-2d/Ff1</a>	FLOWMETER 24VDC 0.5NPTF 4-20MADC/PULSE OUTPUT
<a href="#">Cabinet Coolers</a>	
<a href="#">72f80-Skoaarhab4aw</a>	

<a href="#">83wa02s1sstna</a>	
<a href="#">Tlv Ef73</a>	
<a href="#">Bx17x1700 Li</a>	
<a href="#">Vg1744504114101060103000000003</a>	
<a href="#">Yf115-Aaua1a-S3s3-E/Fmf/Tbl</a>	FLOWMETER 24VDC 0.5IN NPTF 4-20MADC/PULSE OUTPUT
<a href="#">Model: Mcv 11</a>	
<a href="#">A 50</a>	
<a href="#">Vv-Bv-2-G</a>	
<a href="#">208mh</a>	
<a href="#">4040 2800btu 706kcal/Hr</a>	
<a href="#">Hose For 60040a-Nema Type 12</a>	
<a href="#">Model: Mcv 11 S/N: 020111122210</a>	