



Wagner Magnele

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Wagner Magnele Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Wagner Magnele T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
755-EI1	Artikel-Nr.: 1043059 ***** As a replacement for your device type 755-EL110 / 6-1, Device no. 521766 and suitable for your device Type 121-30-8K: 110 we offer you that Succession model to: ***** Version according to list L 755 to control electro magnets for installation in a control cabinet Mains input voltage: 230 volts AC 50/60 Hz. DC voltage magnetic connection: 110 volts Maximum load: 7 amps / 770 watts Degree of protection IP 20 Weight: 3 kg Holding force setting: ...- stufl
Artikel-Nr.: 0216329	Mains choke 2AC 6.0mH 10A Interference suppressor suitable for Umpol control unit Type 755 Nominal voltage 230 V AC / 50/60 Hz. Insulation class: ta = 50 degrees C / B Version: IP00, open, standing up Foot angle Connection via screw terminals Dimensions: 80 x 120 x 60 mm (wxhxd) Weight: 1.4 kg Protection class I
0003584	
0216329	

0280871	
1037506	
1043059	
458022	
752-LT/E16	
752-LT/E30 (Leistungsteil fur elektronisches Umpol-Steuergerat Baureihe 752 Schaltleistung 30 Amp. mit angebautem Kuhlkorper 50 mm breit)	
752-LT/EP30	
752-LT/EP60	
752-ST/1	
752-ST/2	
755	
755-EL110/7-1	
755-EL110/7-1 1043059	
755-EL220/6-1	
755EP10-1-1-230-210-1/1-0	
757-LT/EP30I	
Entstormittel Netzdrossel 2AC 6,0mH 10A	
Koaxialkabel 752-50 kpl.	
Netzdrossel 2AC 6,0mH 10A	
755-EL110/7-1	Electronic polarity reversing device 1043059 Design according to list L 755 for controlling electromagnets for installation in a control cabinet Mains input voltage: 230 volts AC 50/60 Hz. DC magnetic coupling: 110 volts Maximum load: 7 amps/770 watts Protection class IP 20 Weight: 3kg Adhesion force setting: ...-stage
Interference suppression	Mains choke 2AC 6.0mH 10A Article no.: 0216329 suitable for polarity reversal control unit Type 755 Nominal voltage 230 V AC / 50/60 Hz. Insulation class: ta = 50 degrees C/B Design: IP00, open, standing on foot bracket Connection via screw terminals Dimensions: 80 x 120 x 60 mm (w x h x d) Weight: 1.4 kg Protection class I
755el20061	MODULE