

Walvoil

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Walvoil Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Walvoil T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
VMP/B/L 5-38/TS.S	1111021104 230-0030-0210 3/8 "adjustable 50-220bar cap nut Pressure relief valve-directly operated-aluminum housing-max. 210bar-35l / min. Weight: 0.4800 kg / 0.4800 kg Item number: 84812010 Country of origin
VDFR 38-12	230-1410-4625 3/8 "pitch 1: 1 fixed Flow divider Aluminum case-Max. Working pressure210bar-4-12l / min. Weight: 0.8500 kg / 5.1000 kg Item number: 84812010 Country of origin: EU
PBL6/VMP 38/5.TR.S/ac	Z230-00031-99999 1114022100 3/8 "adjustable 180-350bar cap nut Connection block-Cetop 03-with DBV-steel housing-max.350bar-35l / min. Weight: 0.1980 kg / 0.1980 kg Item number: 84812010 Country of origin: IT
VUC 100/Pa0,5	Z230-00178-99999 1 "opening pressure 0.5 bar fixed Check valve-steel housing-max.300bar-150l / min. Product number: 84812010 Country of origin: IT
DPX160 PWM KIT 8EB34LHF3 -24VDC	
DPX160 UL350	

DPC200 PRESSURE RELIEF	
DPX100-DPX160 - INLET COVER SAFETY VALVE (TGW4-250)	
DPX160 - SLICE ORING COMPLETE VITON	
230-0060-5550	1114021102 PBL6 / VMP 38 / 5.TS.S. 3/8 "adjustable 50-220bar cap nut Connection block-Cetop 03-with DBV aluminum housing-Max. Working pressure 210bar-35l / min.
231-800-02100	VEB-12-NC-NOT-24VDC 2/2-way seat valve in the body 1/2 " - 24VDC-Alu Screw-in cartridge: EC10M / 20TB - 2/2-way poppet valve "NC", normally closed with emergency manual operation (Screw) - one side tight / open - pilot operated - conical seat - -70l / min - max.380bar Body: 2-way / SAE-10 / G-1/2 "aluminum - 60mmx60mmx35mm - max. 210bar Magnet coil BER: 24VDC - square - L: 38.5mm, W: 36mm, iØ13.2mm Associated cubic connector: black: 730-010-1000 gray: 730-010-1050 transparent with LED: 730-010-1200 ATTENTION, CUBE PLUG NOT INCLUDED IN THE DELIVERY
231-850-02100	VEB-12-NC-NOT-24VDC 2/2-way seat valve in the body 1/2 " - 24VDC-Alu Screw-in cartridge: EC10M / 20TB - 2/2-way poppet valve "NC", normally closed with emergency manual operation (Screw) - one side tight / open - pilot operated - conical seat - -70l / min - max.380bar Body: 2-way / SAE-10 / G-1/2 "aluminum - 60mmx60mmx35mm - max. 210bar Magnet coil BER: 24VDC - square - L: 38.5mm, W: 36mm, iØ13.2mm Associated cubic connector: black: 730-010-1000 gray: 730-010-1050 transparent with LED: 730-010-1200 ATTENTION, CUBE PLUG NOT INCLUDED IN THE DELIVERY
231-800-01700	VEB-38-NC-NOT-12VDC 2/2-way seat valve in the body 3/8 " - 12VDC-Alu Screw-in cartridge: EC08M / 20TB - 2/2-way poppet valve "NC", normally closed with emergency manual operation (Screw) - one-sided tight / open - pilot operated - conical seat - 40l / min - max.380bar Body: 2-way / SAE-08 / G-3/8 "aluminum - 50mmx50mmx30mm - max. 210bar Magnet coil BER: 12VDC - square - L: 38.5mm, W: 36mm, iØ13.2mm Associated cubic connector: black: 730-010-1000 gray: 730-010-1050 transparent with LED: 730-010-1200 ATTENTION, CUBE PLUG NOT INCLUDED IN THE DELIVERY
231-850-01700	VEB-38-NC-NOT-24VDC 2/2-way seat valve in the body 3/8 " - 24VDC-Alu Screw-in cartridge: EC08M / 20TB - 2/2-way poppet valve "NC", normally closed with emergency manual operation (Screw) - one-sided tight / open - pilot operated - conical seat - 40l / min - max.380bar Body: 2-way / SAE-08 / G-3/8 "aluminum - 50mmx50mmx30mm - max. 210bar Magnet coil BER: 24VDC - square - L: 38.5mm, W: 36mm, iØ13.2mm Associated cubic connector: black: 730-010-1000 gray: 730-010-1050 transparent with LED: 730-010-1200 ATTENTION, CUBE PLUG NOT INCLUDED IN THE DELIVERY
11C90016	
Z230-00635-99999 1565041102 Lowering brake valve-double-	

VODL/SC/CC 34/TR.S.p7	acting-aluminum housing-max.210bar-120l / min.-setting range 50-350bar
VOSL/SC/CC 34/TR.S.p7.PG	Z230-00143-99999 1525041102 3/4"-Öff.v. 1:7 Lowering brake valve-single-acting-aluminum housing-max.210bar-120l / min. Can be used for closed centers
1/2" H-P 4-WAY VALVE	
Z258-00660-99999	181540001 SVM510-B / 00001C hydraulic pilot control unit
VUPSL 38/p3	check valve 3/8" Qmax = 35 l/min - Pmax = 400 bar Weight: 0.9210 kg / 0.9210 kg Commodity number: 84812010
4CAV70 3000	
5116	
511604	
51160892	
51161094	
BC16A/302B	
BETCS24VDC	
DFE 10/3B 18ES.Y201-24VDC	
DFE20/3A18ES-Y201	
DH10/4A	
ER08M/10NB	
O1210021101	
OD150618A000000	
SD25/3	
SDS180/4	
VABAL/SF38/TR.SP3	
VDFR-40S	
VE/B/VMP/VUI/SR38/NC/TS.S/EC08M	
VEB12NC + BTCS24VDC	
VODL/SC/CC 34S	
VOSL/SC 12 1/2	
VPR/3/ET/VMP 34/L/03.TR/ac	
VPR3ET12	

VUS 34	
V-VEP34/TS-TV.S-17	
YAR12400	
VDFR 34-90	230-1440-4655 3/4" division 1:1 fixed Current divider aluminum housing-max. 210bar-40-90l/min. Weight: 2.1500 kg / 2.1500 kg Item number: 84812010 Country of origin: EU
Special Proportional Joystick - DPX 160	
181121065	SVM100/1-B/10G3-00001Ax2 Hydraulic - pilot valve element Connections P + T on the side Rest in neutral Commodity number: 84819000 Country of origin: IT
Lower chain case - 1 set - PM 180 rotary table	
Hydraulic handle - 4 nos - 3 and 5 tons vinches	
Upper chain case lower sprocket -	
SD11/5	
SVM100-1	
80 lt/ dk P-T-C 3/4", A-B 1/2"	SDM 140/3 Elektropnomatik 24V DC +CO (AE =180 Bar)
160 lt/ dk A-B-P 3/4" T 1"	SD18/3 Elektropnomatik 24V DC + (AE =180 Bar)
45 lt/ dk A-B-P 3/8" T 1/2"	SD5/2 Mekanik (AE =180 Bar)
230-0090-0591	1116041102 VMP/VE 34/NA/03.TS.S/EC08M zgh. Solenoid BER Weight: 1.2100 kg / 1.2100 kg Item number: 84812010 Country of origin: EU + 230-1780-4050 Solenoid BER - 12 VDC 4SLE001200A
Z251-10888-99999	102211504 SD5/2-P(KG3-120)/1CS8L/1CS8L/AET 2 section monoblock valve 45l/min-315bar 2-section monoblock valve 45l/min-315bar - connections 3/8" - DBV 60 - 200bar - hand lever actuated 1st section: double-acting with fine control slide max. 30 l/min. 4/3-way - middle position: A+B closed+pressureless circulation-spring centered in 0 2nd section: double-acting with fine control slide max. 30 l/min. 4/3-way - middle position: A+B closed+pressureless circulation-spring centered in 0
VDFR 34-90	230-1440-4655 3/4" division 1:1 fixed Current divider aluminum housing-max. 210bar-40-90l/min. Weight: 2.1500 kg / 2.1500 kg Item number: 84812010 Country of origin: EU
SELF LEVEL VALVE(VCF12/SE GHISA)	VCFL 12/SE10ASAEGHISA-WITH FLOAT BYPASS P/N:1992033208
3/4" VUS34 0,5 BAR CHECK VALVE	
1/2" VUS12 0,5 BAR CHECK VALVE	
ERGONOMIC JOYSTICKSVM 400	TYPE+DEAD MAN WITH DETENT FOR FLOAT P/N:181420484

JOYSTICK- SLOPED	SERVOCOMANDO SVM400-EMD1/7 1-S/01E 15HMB03G-1R4040-4R3040-5R2040-.....12VDC
PILOT CONTROL VALVE	FEED UNIT 6 VALVE BLOCK FU-NA-NR-A-NV/6-EJ08F/NPM-BSP-12VDC P/N:DFRI15025
TRAVELING JOYSTICK SVM430/23-B/01HA049-0RD040	SVM430/23-B/01HA049-0RD040 P/N:181430056
250A-125-01340	5LEV110000S S10/LSG lever housing Lever housing aluminum for hand lever M10 - SD11+SD14+SDS150+SD16+SDS180+DLS16+DLS180 Weight: 0.2809 kg / 2.8090 kg Item number: 84819000 Country of origin: EU
1720021105	VE/B38/NC/EC08M 3/8" 2/2-way poppet valve-with emergency manual-currentless E to U closed / energized E to U open aluminum housing max. 210bar-40l/min. Solenoid: BT
SVM510-520-521	
250A-130-01200	4SOL412024-C Magnetspule D12C - 24VDC Magnetspule für ISO-Stecker Magnetspule eckig für SD4, SD5, SDE030, SDE060B L: 50mm, B: 35mm, iØ: 19,15mm Spannung: 24 VDC ±10% Einschaltdauer: 100% Schutzklasse: IP65 Leistungsaufnahme: 36 Watt max. Stromaufnahme: 1,5 Ampere Zugehöriger Würfelstecker: Schwarz: 730-010-1000 grau: 730-010-1050 transparent mit LED: 730-010-
VO SL/SC/CC 34/TR.S.p7.PG	Z230-00143-99999 1525041102 3/4" f.f. 1:7 Lowering brake valve-single-acting-aluminum housing-max.210bar-120l/min. Can be used for closed center Goods number: 84812010 Country of origin: IT
Art.183520154 (14308800019) JOYSTICK	
Z257-02106-99999	183540004 Joystick AJW P-Handle - 1x thumbwheel 1x button FNR with deadman button Joystick base AJW for handle P Supply voltage: 8 - 32V Output: 0.5 - 4.5V Line: 35 cm Connector: German DTM06-12S Position W: Thumbwheel Position Z: button FNR Position 0: red deadman button
1814200001	repair kit
SVM510-B/00001C	181540001 Z258-00660-99999
254-030-01161	12Z640025 DFE20/3A18ES-W200-24VDC-CRZ 3/4"-140l/min.-200bar Galvanized 3/2-way switching valve Connection size P + A + B: 3/4" Max. working pressure: 200bar Actuation: directly electrically operated 24VDC / 60W with ISO4400 contacts - on the side of connection "A" Switch position 1: P + A connected and B blocked Switch position 2: P + B connected and A blocked Switch overlap: negative
230-0320-1420	1210031101 VDA 12/TR.S.VRR 1/2" adjustable 100-250bar cap nut Shut-off valve (accumulator) aluminum housing - max. 250bar-50l/min. non-return valve with steel seat
	1210032101 VDA 12/TR.S.VRR/ac 1/2" adjustable 100-250bar

230-0320-1425	cap nut Shut-off valve (accumulator) steel housing max. 350bar-50l/min. non-return valve with steel seat
VOSL/SC/CC 12/TR.S.p7.PG	Z230-00146-99999 1525031102 1/2"-opening 1:7 - 50-350bar(max.210) - 75l/min. Lowering brake valve-single-acting-suitable for closed centers-aluminum housing Weight: 1.0300 kg / 2.0600 kg Item number: 84812010 Country of origin: IT
VBCD12-SE-A-CC	Lowering brake valve - single-acting - partially relieved - Connection size: 1/2" Max. flow rate: 60l/min Control ratio: 1:4.5 Setting range: 100-350 bar Maximum pressure: 350bar Adjustment lock with counter nut and cap nut Spring space relieved Used when the upstream directional control valve has ports A+B blocked in the neutral position are. Weight: 1.2280 kg / 2.4560 kg Item number: 84812010 Country of origin: IT
230-0500-1885	1230021125 VRPRL 38/TV.S 3/8" adjustable 40-110bar cap nut Pressure reducing valve-with leakage oil connection+with bypass check valve-aluminum housing-max. 210bar-20l/min.
205-045-01250	V0705/C180 VRPRL38/35-180 Pressure reducing valve with leakage oil connection and bypass check valve - directly controlled Connection size: 3/8" Max. flow rate: 30l/min Setting range: 35-180 bar Maximum pressure: 350bar Adjustment lock with lock nut
254-130-01200	122054050 DF5/3AC17CB 3/8"-60l/min.-315bar 3/2-way switching valve Connection size P + A + B: 3/8" Actuation: rollers operated via brass roller Ø 22mm - on the side of connection "B" Positioner: spring return in switching position 1 - on the side of connection "A" Switch position 1: P + B connected and A blocked Switch position 2: P + A connected and B blocked Switch overlap: negative
230-0320-1420	1210031101 VDA 12/TR.S.VRR 1/2" adjustable 100-250bar cap nut Shut-off valve (accumulator) aluminum housing - max. 250bar-50l/min. non-return valve with steel seat
258-041-02000	3CAS105746 DFE052/6B Slider 6 ways DFE052-slider-unswitched A to E + B to F open-positive switch overlap Just the slider
Z257-02281-99999	183334031 CED400X proportional control for 8 coils
SDS150/5 - VALVE, HYDRAULIC,	3 PIECES WITH DETANT- 2 PIECES ABT
CODE : 12G060032	DFE100/6B18ES-W 24DB1-14VDC-CRZ DİVERTER VALVE 51592128 -1 Jahresbedarf
Z230-00146-99999	1525031102 VOSL/SC/CC 12/TR.S.p7.PG 1/2"-Öff.v. 1:7 - 50-350bar(max.210) - 75l/min. Lowering brake valve, single-acting, suitable for closed centers, aluminum housing
230-0310-1400	1210021101 VDA 38/TR.S.VRR 3/8" adjustable 100-250bar cap nut Shut-off valve (accumulator) aluminum housing - max. 250bar-25l/min. check valve with steel seat

230-0310-1405	1210022100 VDA 38/TV.S.VRR/ac 3/8" adjustable 5-110bar cap nut Shut-off valve (accumulator) steel housing - max. 350bar-25l/min. check valve with steel seat
Z258-00782-99999	18Z010173 SV01-B
258-040-26250	3CU2410120 SDS150/1 Slider SDS150
Z258-00449-99999	5CR6A1135RM KIT CURVA A1135R-MM Kinematik-Kit
12869	
24VDC DPC130 8ZR4PD	
258-020-01350	4SOL519112-C Solenoid coil D19C - 12VDC Solenoid coil for ISO connector Round solenoid coil for DFE102 and DFE20 L: 75mm, aØ: 65mm, iØ: 31mm Voltage: 12 VDC ±10% Duty cycle: 100% Protection class: IP65 Power consumption: 60 watts Max. current consumption: 5 amps Related cube plugs: black: 730-010-1000 gray: 730-010-1050 transparent with LED: 730-010-1200
257-010-01250	183540009 Joystick-8 functions-right hand 4x prop.+ 1 rocker (prop.) + 2 buttons (on/off) AJWPZTB2100EC/D2F12150
230-1280-3941	1624021100 VPR/3/ET 38+VMP+VE.NA/V/02.TS/EC08M 3/8"-EB: 50-220bar-handwheel Flow control valve 3-way-pressure compensated-remaining quantity without pressure to the tank-with pressure relief valve-with 2/2 way relief valve (normally open-coil BE)-aluminum housing-max. 210bar-50/30l/min. Solenoid coil BER
181121065	Z258-00665-99999 SVM100/1-B/10G3-00001Ax2 Hydraulic pilot valve element Ports P + T on the side
Dpc 130/6	
Vpr/3/Et 12-Mg	
Vpr/3/Ep 12/L	
Df10/3a17slp / 254-140-01100	
Od150618a000000 2wv Noe 350[]bar-40l/Min [h] Nscca-08a-2n [od150618a000000]	
Sd14/1 3/4" 250 Bar 120 Lt	
Vabal/ Sf38 Control Valve	
Veb12nc + Btcs24vdc 2/2 Valve	
Sds/2 Ac Yg4-220 18l*3rc	
Sd25/3 Wegeventilp0723688117300029	
Dn25-4/3 Sd25/1	
250-060-02200 Sdm140/5-P(Yg3-175)	

Vosl/Sc 12 1/2 Ventil Bremse Montage Der Tuben	
Plb6/Wmp38	SD1-2 TANDIS HEIZUNG PRESS.RELIEF.VALVE
Oc5101017	
Mg10a/0s2b	
Sd5/1-D(Kg3)/28l	
5v08130902	
1720042102	
5v08130900-Obsolete	
Vda12	
Vuc100	
252-070-03600	
Vpr/3/Ep 12/Mg/Ac	
Kreuzhebel Mit Hohlstange - Seilzugsteuerung, 179040002, Scf031/02v004	
1210041101	VDA 34 / TR.S.VRR 3/4 "setting 100-250bar cap nut Shut-Off Valve (Tank) Aluminum body-max.250bar-100l / min. Check valve with steel seat
Pm1302785	
230-0310-1400 Vda 38/Tr.S.Vrr	
252-070-03300	
Halteventil	
Vosl/Sc 1/2quot;	
Svm510	Z258-00441-99999 5CIN5003 SVM510 Pedal 258 Valve Items W
230-0960-2940	
Bc16a/302b Valve	
252-070-02150	
Vpr3et12 Flow Control Valve 2/2 Valve	
Vpr/3/Ep 12/Mg	
Sd 6/2 Ac(Yg4-215)18l*2/Rc	
1101808	

Voslþ 100/Tr.S.P7/Ac	
Vuc114	
Dh10/4a Vierweg Plugkraan	
Sd 11/1-Sv/111 L	
Vuc34	
VbpdL 34/P4	230-0800-2610 1420041100 VBPD L 34 / p4 3/4 "opening: 4.5 Check Valve Double Acting Unlockable-Aluminum Casing- max.210bar-100l / min. 230-pipe valves O
Sds150/1/Ac(Xg3-125)/P-18l/Rc	
243876 Vda 12/Er.S.Vpp 1210031101	
5cr6a1135rm	Z258-00449-99999 Valve item KIT CURVA A1135R-MM main bearing
230-0500-1880	
1230021102	
Er08m/10nb Walvoil 4/2 Cartridge Er08m/10nb210 Bar20 Liter / Minute	
1992751112	
Dhv080/8In-Sae-Crvn	
Al01/M10x200	
Vep 34/Tr-Tv.S Pressure Block	
Oe150009	
150-S-3/4-Ipm-35-Ap Hydraulic Brake	
VbpdL 38/P4	
Vpr/3/Ep 12/L/Ac	
Sd25-2	
Dhv080/8In-Crvn	
Art.183520154	Joistik--14387700120 -46.30.000980.01 ART.183520154 PX.1400539\001 19\14
Vmp/Ve 12/Na03/Ts.S	
Svm400	
Sds150/2/Ac(Xg3-125)/P-18l/P-18l/Rc	
Vodl/MI/10-12	

5lev138700 Dpc38 Pk11110542 Vdfr-40s Flow Divider Housing (Steel)
252-070-01000
Ve/B 34 Na
Gjs1-B3t4
5v08140902
Vpr/3/Ep 12/V
Dfe 10/3b 18es.Y201-24vdc Ventil Magnetventil
258-030-01450 170012020
Sd4/1 Sv 112
Od410303040000
256-040-02200
Sds180/4 Wegeventil P0906272115400036