



## Warom

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Warom** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Warom T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">Bny81-36x2x (2x36w) Ex</a>	
<a href="#">Bjd81-Y 220v Ac 50/60hz</a>	Explosion-proof Caution Spotlight Fittings 220V AC1.Ex mark:II 2 G Ex d IIC T6 Gb II 2 D Ex t IIIC T80°C Db IP66 2.Enclosure:copper-free aluminium alloy, powder coated surface, yellow(RAL 1021) 3.Rated voltage:220V AC 50/60Hz; 4.Lamp power:3W 5.Degree of protection:IP66 6.Ambient temperature:-40°C~+55°C 7.Please refer details to WAROM Catalogue 2020
<a href="#">Bjd81-Y 24vdc</a>	1.Ex mark:II 2 G Ex d IIC T6 Gb II 2 D Ex t IIIC T80°C Db IP66 2.Enclosure:copper-free aluminium alloy, powder coated surface, yellow(RAL 1021) 3.Rated voltage:24V DC 4.Lamp power:3W 5.Degree of protection:IP66 6.Ambient temperature:-40°C~+55°C 7.Please refer details to WAROM Catalogue 2020
<a href="#">Bzc 8050-40092ba-96</a>	
<a href="#">Bza8050-A2-40066 / ATEX</a>	
<a href="#">BDD81-A100X</a>	
<a href="#">BYA 51-36x2x</a>	
<a href="#">BNY81-LED-2X18 WATT</a>	
<a href="#">BZA8050-A2D1</a>	Explosion-proof Control Unit Systems ATEX 1. Ex-mark: II 2 G Ex d e IIC T6 2. Enclosure: GRP, in black 3. Rated voltage: Max. 415V AC 4. Rated current: 10A 5. Degree of protection: IP65 6. Ambient temperature: -20°C~+55°C 7. Cable entries: 1 x M25 x 1.5 cable gland 8. Details refer

	to catalogue
<a href="#">BAZ8050-A1D1</a>	Explosion-proof Control Unit Systems 1. Ex-mark: II 2 G Ex d e IIC T6 2. Enclosure: GRP, in black 3. Rated voltage: Max. 415V AC 4. Rated current: 10A 5. Degree of protection: IP65 6. Ambient temperature: - 20°C~+55°C 7. Cable entries: 1 x M25 x 1.5 cable gland 8. Details refer to catalogue
<a href="#">15092021681</a>	BZA8050 A2D1 CTP 415 V AC Atex IP65
<a href="#">Model : BAYD-B-F</a>	Ex-Proof Wall Mounted EXIT Luminaire with Aluminum Cast Body, Tempered Glass Resistant to Thermal Shocks and Impacts, Electronic Ballast, 120 Minutes Capacity Battery
<a href="#">BBJ81-R / ATEX</a>	1.Ex-mark:II2 G Ex d ib IIC T6 Gb II2 D Ex t IIIC T80°C Db IP66 2.Enclosure:Copper-free aluminium, powder coated surface,yellow(RAL1021) 3.Rated voltage: 220-240V AC 50/60Hz 4.Lamp power: 5W LED 5.Lamp colour: Red 6.Ambient temperature:-40°C~ + 55°C 7.Cable entry: 3×M25×1.5 plugs 8.Degree of protection:IP66 Please see detail to catalogue 2022. Explosion-proof Audio and Visual Caution spotlight fittings
<a href="#">EXPROOF IICT4 16A 380VAC</a>	
<a href="#">BAK51-50/240B</a>	
<a href="#">BBJ81-R</a>	
<a href="#">BBJ81-R</a>	BBJ81-R, 220VAC, 100-120dB, Red, Explosion-Proof, IP66
<a href="#">30008.</a>	
<a href="#">Bak51-50/240b</a>	
<a href="#">Bay-H21x1</a>	
<a href="#">Bcz8060-16/250/3p/Z</a>	
<a href="#">Bayd-Bf</a>	
<a href="#">Bza8050-A1</a>	
<a href="#">Yk18df-2cs</a>	
<a href="#">Bjd-Z</a>	
<a href="#">Bsx-60 E27 Lamp Holder</a>	
<a href="#">Bcz8060-16/250/3p</a>	
<a href="#">Bat51 - Hie400</a>	
<a href="#">Explosion Proof Portable E-26 220v 100w Obsolete Replacement Bsx-60</a>	
<a href="#">Dqm- Ii/M20x1.5 (708001)</a>	
<a href="#">Bay51-D-236</a>	EX-PROOF ALUMINUM BODY 2X36 W
<a href="#">5136019</a>	
<a href="#">Bdh51-C/M20 X 1.5</a>	
<a href="#">Cdz-Hr160-1560-Qd</a>	
<a href="#">Bat53-400-Hie400</a>	
<a href="#">Bzm-16b</a>	EX-PROOF Switch
<a href="#">Baz51 - Hie400</a>	

<a href="#">S_Series</a>	4 INSERT BUGS
<a href="#">Bhd51-A M25x.5</a>	
<a href="#">Bay51-Q36x2x</a>	
<a href="#">Bbj81-R Dc 24v</a>	
<a href="#">Bzc8050-A1g</a>	
<a href="#">Bbj81-R24</a>	
<a href="#">Dqm- Ii/M20x1.5 (709002)</a>	
<a href="#">Bat86-160-120g</a>	100 Watt – 100-300V – IP66, CLASS II
<a href="#">Bxj-Iib-Iv</a>	
<a href="#">¾" Ex-Proof Fittings</a>	
<a href="#">BBJ81-R</a>	Explosion-proof Audio and Visual Caution spotlight fittings ATEX 1.Ex-mark:II 2 G Ex d ib IIC T6 Gb II 2 D Ex t IIIC T80°C Db IP66 2.Enclosure:Copper-free aluminium, powder coated surface,yellow(RAL1021) 3.Rated voltage: 220-240V AC 50/60Hz 4.Lamp power: 5W LED 5.Lamp colour: Red 6.Ambient temperature:-40°C~ +55°C 7.Cable entry: 3×M25×1.5 plugs 8.Degree of protection:IP66 Please see detail to catalogue 2022 page2/161.
<a href="#">Bay51-D-258</a>	
<a href="#">Bjd-Gr</a>	
<a href="#">Bhd51-B/M20x1.5</a>	
<a href="#">Bjd-Gy</a>	
<a href="#">Yk36df-2cs</a>	
<a href="#">Bad 85-120-120-D</a>	
<a href="#">Bza8050.....Ex</a>	
<a href="#">Bcz85-16-250-3p</a>	EX-PROOF MONOPHASE Plug-in
<a href="#">Bzx-6</a>	
<a href="#">Bat86-160-120y</a>	
<a href="#">Bbj81-Y</a>	