



Waycon

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Waycon** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Waycon T¼rkiye Distrib¼t¼r¼ veya temsilcisi deđildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
172805272	
SX80-2500-420A-SA12-IP67	Draw wire displacement transducer, measuring range: 2500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.1%, 4-pin axial M12 connector output Option: increased protection class IP67
SX50-500-420A-SA12-IP67	Draw wire displacement transducer, measuring range: 500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.15%, 4-pin axial M12 connector output Option: increased protection class IP67
SX50-250-420A-SA12	Draw wire displacement transducer, measuring range: 250 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output
SX50-375-420A-SA12	Draw-wire transducer, measuring range: 375 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output
MAB-A-A-900-E	Magnetostrictive displacement transducer, rectangular profile, IP67, Measuring range: 900 mm, linearity: max. ± 0.01%, Output: 4...20 mA, 5-pin connector output M12
SX50-150-420A-SA12	Cable displacement transducer, measuring range: 150 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output

SX50-125-420A-SA12	Cable displacement transducer, measuring range: 125 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.5%, 4-pin axial M12 connector output
LRW-M-275-S	Linear potentiometer with push rod (M6), rectangular profile, measuring range: 275 mm, linearity: ± 0.05%, IP60, resistance: 5 kOhm, 4-pin connector output
PMX-24	Signal converter for potentiometer, Output: 4..20 mA / 10 V / 5 V / ±10 V / ±5 V configurable, Supply: 9...36 VDC, galvanically isolated, with cable break detection and alarm output, for DIN rail
SX50-750-420A-SA12	Cable pull transducer, measuring range: 750 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.1%, 4-pin axial M12 connector output
SX50-250-420A-SA12-M4	Cable pull transducer, measuring range: 250 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output Option: Cable fastening, M4 terminal
K4P2M-SW-M12	4-pin cable socket, M12 angle connector including 2m cable, shielded. Cable end 40mm stripped, shield braid twisted and strand ends provided with insulated wire end ferrules.
UR2	Deflection pulley ø 44 mm, ball bearing, Operating temperature - 40...80°C
LVIG-100-420A-KR01	
LVIG-50-420A-KR01	
Sx80-2000-420a-Ka02	
Sx50-500-420a-Sa12-IP67	Pull-wire position transducer, measuring range: 500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.15%, 4-pin axial M12 connector output Option: increased protection class IP67 Tariff No .: 90318020 Origin: DE Weight: 0.30 kg Prefix: YES
Wp -6,8t-420a-Ka02 Lenkwinkelsensor	
Sx80-2500-420a-Sa12-IP67	Pull-wire position transducer, measuring range: 2500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.1%, 4-pin axial M12 connector output Option: increased protection class IP67 Customs Tariff No .: 90318020 Origin: DE Weight: 0.80 kg Prefix: YES
Sx80-1000-420a-Sa12 Sensor	
Lzw-M-500	
Sm25-Hyd-F18-Ka-0	
Rp-M-180-420?-??02 Lenkwinkelsensor	
Wp-90-420a-Sa12	Angle of rotation sensor, anodised aluminum and stainless steel, ø 60 mm, IP67 (on the housing side), IP60 (on the shaft side), Measuring range: 90 °, spin-through, Supply: 12 ... 30 VDC, output: 4 ... 20 mA, Linearity: 0.3%, 4-pin axial connector output M12
Con006	
Sx80-1500-420a-Sa	
Sx50-125-420a-Sa	
Las-Tx-4-420a	
Sr128-015	
Sm10-T-Sa-1312112	

Las-T5-100-V	
Lrw3-C-25	
???-?-?-800-W	
4p-Gegenst.-2kab-Hyd Ptfе-UI Kabel, 2 M, Orangemit Konfektioniertem Gegenstecker, Typ Lemo Phg.0b	
Sx80-3000-420a-Sa-00	
Rx80-2500-420a-Sa12 Sensor	
Lx-Ep 40	
Lzw-M-150	
Sx120-6000-420a-Sa	
K4p2m-S-M12	Cable socket 4-pin, straight M12 plug incl. 2 m cable, shielded. Cable end stripped 40 mm, screen braid twisted, Stranded ends with insulated ferrules provided
Sx80-2000-420a-Sa	
Rx80-1000-Net-Sr12-M4 Profinet,Vers: 10-30vdc,Ip65,L=1000	
Sx50-750-10v-Ka	
Sx50-1000-420a-Sa	
Mss976r-0500I02	
Md20b	
Sm100-Sg-Ka	
Cmss65-002-00-15-10	
Sx200-6-Ssi-Sr23 Seilzug-Wegaufnehmer	
Sx50-375-420a-Sa	
Lrw-M-225-S	
K4p2m-Sw-M12	Cable socket 4-pin, M12 angle plug incl. 2m cable, shielded. Cable end stripped 40 mm, screen braid twisted, Stranded ends with insulated ferrules provided.
Sx50-750-420a-Ka02-Om4	
Sx50-375-420a-Ka02	
Sx50-1250-10v-Sa	
Sx200-6-Ssi-Sr23	
???-?-?-1000-W	
Imca-24v-420a Lvdt-Externelektronik F. Din-Schiene, Versorgung: 9...36 V, Ausgang:4...20 Ma	
Zx-Pa-1,5-A Bewegungserfassungs	
Sensor Lineartechnik Mav-A-A-250-E	

Lam-F-200-Hd Lasersensor	
Ima2-Lvdt3a-24v	SIEHE ANHANG
Las-T5-500-V	
Sx50-500-420a-Sa	
Sm10-T-Sa-1112112	
Lzw-M-300	
Rp-M-90-420a-Ka02 Lenkwinkelsensor	
Sx135-10-420a-Ka	
Rx120-4000-Net-Sr12-M4 Wegaufnehmer Seilzug	
Sx50-1000-1r Sa	
Kab24-420a	
Ps-100-240ac/24dc/1.3	
Mg10-P1 Main-Modul Com-, Versorgung: 12- 24vdc Rs232c	
Rx80-1000-Net-Sr12-M4 Wegaufnehmer Seilzug	
Ras-Tx-4-420a Laser-Wegaufnehmer	
Sx80-3000-420a-Ka02	
Sx80-8000-420a-Ka02	
Sx50-1000-420a-Ka	
K4p2m-S-M12-Cat Kabel Mit Stecker	
Imca-24v-10v	
Ha705lk-905	
Sx50-375-10-Sa	
Sx50-225-420a-Sa	
???-20-26-10-10 Kupplung	
Ima-24v-420	
Sx80-3000-Srm50	
Sx120-4000-420a-Sa	
Sm25-Hyd-T-Sa-F18	
Sx80-2000-420a-Ka	
Sx80-2500-420a-Sa	
Sx80-2500-1-G-Sr	
D4-W-M12-S Verbinder	
Rm15-Wtja-8s	

Pmx-24 Sensor	
Lzw2-F-50	
Sm25-T-Ka-H-Ks	
Sm140-Hyd-H-18-Ks	
Sm50-Hyd-T-Ka-L20-F18	
Rx80-2000-Net-Sr12-M4 Wegaufnehmer Seilzug	
Sx50-500-420a-Sa-0	
Sx50-1000-420a-Ka02-Om4	
Con011	
Sx80-3000-420a-Sa-O Imal S00128	
Sm25-T-Sr	
Wp-320-10v-Ka02 Analoger Drehwinkelsensor	
Sx80-1500-420a	
Rx80-2000-10v-Sa12 Bewegungserfassungs	
Rp-15t-420a-Sa12 Lenkwinkelsensor	
Imca-24-420a	
K5p2m-S-M12 Kabel Mit Stecker	
Rm15-Wtpa-8p	
Sx50-50-420a-Sa	
Sx50-375-420a-Sa12	Pull-wire position transducer, measuring range: 375 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output Tariff No .: 90318020 Origin: DE Weight: 0.30 kg Pref .: Yes
110294	
Sx80-3000-420a-Sa-O	
Sx50-125-420a-Sa12	Pull-wire position transducer, measuring range: 125 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, IP 65, Linearity: 0.5%, 4-pin axial M12 connector output Tariff No .: 90318020 Origin: DE Weight: 0.30 kg Prefix: YES
Mss976r-0400I03	
Zx-Hm-1,5-A Bewegungserfassungs	
Sx50-300-420a-Ka	
Sx50-125-420a-Ka02	
Sx80-2000-420a-Sa Kabeltrommel Sensor	
Lzw1-F-75	
Sx80-1000-Pro-K1	
Imca-24v-420a	

Sx80-1500
Sx120-6000-Pro-M12-O-S1-K1
Sx50-225-10v-Ka02
Con012-S
Sx50-750-420a-Ka02