

W.E.St.

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
W.E.St. Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız W.E.St. T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Pam-199-P Version 2230	GL TYPE APPROVAL, Certificate No. 11251 - 14 HH - ersetzt die PAM-195, 196 und 197 / replaces PAM-195, 196 and 197 - universeller Leistungsverstärker / universal power amplifier - USB Schnittstelle / USB interface - für Wege-, Druck- und Drosselventile / for directional, pressure and throttle valves - 0,5... 2,6 A Nennstrom (stufenlos einstellbar) / 0,5... 2,6 A rated current (infinitely adjustable) Zolltarif Nr. / HS-Code: 85437090
W.E.St.	
W.E.St.	
W.E.St.	
W.E.St.	
PAM-199-P	GL TYPE APPROVAL, Certificate No. TAA00002Yes - replaces the PAM-195, 196 and 197 / replaces PAM-195, 196 and 197 - universal power amplifier - USB interface / USB interface - for directional, pressure and throttle valves / for directional, pressure and throttle valves - 0... 2.6 A rated current (continuously adjustable) / 0... 2.6 A rated current (infinitely

	adjustable)
PAM-195-P-S3	Revision 2230 - digital power amplifier / digital power amplifier - 0... 10 V, +/- 10 V or 4... 20 mA input signal ranges / input signal ranges - USB interface / USB interface - with direction switch - integrated power limitation function / integrated power limitation - 0.5... 2.6 A nominal current (continuously adjustable) / 0.5... 2.6 A rated current (infinitely adjustable)
PAM-193-P	Revision 4121 Power amplifier for proportional valves / Power amplifier for proportional valves Parameterization via potentiometer / parametering with potentiometer Current ranges 1.3 A and 2.6 A Reference voltage 8 V
SCU-138-P	Revision 2230 Speed control unit 6 kHz input frequency Rated current adjustable up to 2.6 A/ rated current adjustable up to 2.6A 1 x programmable setpoint / 1 x programmable command value 1 analogue setpoint input / 1 x analogue input signal Switchable to PWM setpoint input / switchable to PWM setpoint input Customs Tariff No. / HS Code: 85371098
PAM-190-P-I	Version: 1322 Plug amplifier / power plug 4... 20 mA input signal 2.5 A maximum output current Adjustable: PWM frequency, MIN, MAX and ramps / adjustable: PWM frequency, MIN, MAX and ramps
PAM-199-P	GL TYPE APPROVAL, Certificate No. TAA00002Yes - replaces PAM-195, 196 and 197 / replaces PAM-195, 196 and 197 - universal power amplifier / universal power amplifier - USB interface / USB interface - for directional, pressure and throttle valves / for directional, pressure and throttle valves - up to 2.6 A rated current (infinitely adjustable) / up to 2.6 A rated current (infinitely adjustable)
Dsg-164-30	
Pam-191 Power Amplifier	
Pam-199-P	Version 2130 (new design) GL TYPE APPROVAL, Certificate No. 11251 - 14 HH replaces PAM-195, 196 and 197 / replaces PAM-195, 196 and 197 - universal power amplifier / universal power amplifier - USB interface / USB interface - for directional, pressure and throttle valves / for directional, pressure and throttle valves - 0.5 ... 2.6 A rated current (infinitely adjustable) / 0.5 ... 2.6 A rated current (infinitely adjustable) Tariff no. / Customs tariff no. : 85437090
Pam-196-S8	
Dsg-111-U Version 2030 Wandler	
Sv-200	
Dsg-111-U-2030	