

## Winkel

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Winkel** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Winkel T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">200.012.000</a>	4.073 WINKEL bearing Ø 70.1 mm Can be adjusted axially via discs
<a href="#">Axial roller bearing WINKEL type 4.063 + AP</a>	
<a href="#">Guide profile WINKEL Standard</a>	6NbV L=3200mm (Standard 6NbV L3200 with holes for mounting M16)
<a href="#">Bogen 90° 1/2" AG IG</a>	WINKEL 90Grd AuŐen/Innengewinde 1/2" ohne Bund Art.Nr.: CU3092MS.1/2
<a href="#">200.216.306</a>	3.063 Heavy Duty ANGLE roller Delivery includes - 1 grease nipple M6 x 1 - 1 O-ring - 2 sealing washers 0.5 mm
<a href="#">200.216.304</a>	3.061 Heavy Duty WINKEL roller Delivery includes - 1 grease nipple M6 x 1 - 1 O-ring - 2 sealing washers 0.5 mm
<a href="#">113.016.000</a>	8,96 m U-Profil Standard 6 NbV WINKEL guide profile Number Length 2 4,480.00 mm External dimensions: 201.5 x 71.2 mm Chamber dimensions: 150.1 mm Sandblasted with SA 2.5 blasting pattern Original hot-rolled WINKEL profiles are made from S450 J2 mod. The significantly improved material has

	high strength properties and thus enables a higher load between the roller and the profile. Our sawing tolerances are - up to a length of 2,999 mm ± 1 mm - from a length of 3,000 mm ± 2 mm
<a href="#">113.014.000</a>	113.014.000 U-Profil Standard 4 NbV WINKEL guide profile Number Length 2 3,500.00 mm External dimensions: 157.2 x 61.2 mm Chamber dimensions: 108.4 mm Sandblasted with SA 2.5 blasting pattern Original hot-rolled WINKEL profiles are made from S450 J2 mod. The significantly improved material has high strength properties and thus enables a higher load between the roller and the profile. Our sawing tolerances are - up to a length of 2,999 mm ± 1 mm - from a length of 3,000 mm ± 2 mm
<a href="#">113.016.000</a>	
<a href="#">200.216.304</a>	
<a href="#">200.216.306</a>	
<a href="#">113.014.000</a>	
<a href="#">200.056.000</a>	4.063 + AP 6 ANGLE roller Ø 149.0 mm ANGLE roller permanently welded with screwing plate Screwing plate rectangular 200 x 150 x 20 mm
<a href="#">113.016.000</a>	U-profile standard 6 NbV ANGLE guide profile Number Length 2 7,000.00 mm External dimensions: 201.5 x 71.2 mm Chamber dimensions: 150.1 mm Sandblasted with blasting pattern SA 2.5
<a href="#">3199 10 21</a>	
<a href="#">113.001.000</a>	
<a href="#">113.010.000 0 Nbv Aussenmaã223;E 86,5 X 36 Mm Anzahl Lã196;Nge 4 1.000,00 Mm Sandgestrahl Mit Strahlbi</a>	
<a href="#">4.062</a>	
<a href="#">709370.51.00-01</a>	
<a href="#">4.054+ap0</a>	
<a href="#">113.010.000</a>	
<a href="#">113.011.000 L=3000mm</a>	
<a href="#">Hp10-2-Igf08n</a>	
<a href="#">4.056</a>	
<a href="#">200.055.001 4.061 + Ap 4 Q Kombirolle Å216; 107,7 Mm Fest Verschweiã223;T Mit Anschraubplatte Anschraubpl</a>	
<a href="#">240.100.176</a>	

<a href="#">Jt 2.058</a>	200.210.303 - Ø 88,4 mm just. ANGLE roll unit
<a href="#">113.010.000 L=3040mm</a>	
<a href="#">200.165.000</a>	
<a href="#">113.010.000 L=4500mm</a>	
<a href="#">96510.00.00-25-3</a>	
<a href="#">1022.550.130/4/</a>	
<a href="#">061.073.030</a>	
<a href="#">227.044.000</a>	
<a href="#">3199.06.17 Inkl Fda Zertifikat</a>	
<a href="#">Kb 4.072 P</a>	
<a href="#">Pa20080</a>	
<a href="#">200.163.000</a>	
<a href="#">231.002.000</a>	
<a href="#">2.056</a>	
<a href="#">4.073 Ap-1q</a>	
<a href="#">113.010.000 L=1200mm</a>	
<a href="#">1022.550128/4/</a>	
<a href="#">113.012.001</a>	
<a href="#">1319.40.06-00-3</a>	
<a href="#">4.072p</a>	
<a href="#">201.035.000</a>	
<a href="#">3166.06.10</a>	
<a href="#">200.105.000, Pr 4.062 Winkel-Rolle Ä216; 127,8 Mm</a>	
<a href="#">3139.06.00</a>	
<a href="#">4.058+ap3</a>	
<a href="#">290.004.000</a>	
<a href="#">113.015.002 Prã196;Zisionsprofil Pr 5 Nbv Aussenmaã223;E 175 X 64 Mm Anzahl Lã196;Nge 4 1.000,00 Mm</a>	
<a href="#">113.014.000</a>	
<a href="#">200.105.000 Pr 4.062 Kombirolle Ä216;</a>	

<a href="#">127,8 Mm</a>
<a href="#">200.101.002</a>
<a href="#">Kb 4.073</a>
<a href="#">3116.06.00</a>
<a href="#">Jc 4.054</a>
<a href="#">709370.41.00-01-4</a>
<a href="#">3199.10.17</a>
<a href="#">200.003.000</a>
<a href="#">113.022.001</a>
<a href="#">19439.01.02-02-3</a>
<a href="#">290.003.000</a>
<a href="#">Mr1942</a>
<a href="#">200.076.001</a>
<a href="#">205.064.000</a>
<a href="#">200.001.000</a>
<a href="#">212.004.000</a>
<a href="#">Mr1941</a>
<a href="#">U-Profil Standard 0 Nbv</a>
<a href="#">113.013.000 Aussenmaã223;E 135,4 X 53 Mm Anzahl Lõ;Nge 2 10.000,00 Mm Sandgestrahlt Mit Strahlbild Sa 2,5 Gewicht 572,00 Kg</a>
<a href="#">225.000.000(W2r.230.06.Xx 1106kd Dkol-10l)</a>
<a href="#">200.015.002</a>
<a href="#">205.062.000</a>
<a href="#">3nb</a>
<a href="#">113.014.000 4 Nbv Aussenmaã223;E 157,2 X 61,2 Mm Anzahl Lã196;Nge 4 1.000,00 Mm Sandgestrahlt Mit Strahl</a>
<a href="#">3199.08.17</a>
<a href="#">4.072 P</a>
<a href="#">205.093.001</a>
<a href="#">201.012.000</a>

<a href="#">201.055.001</a>
<a href="#">Ds-3-05</a>
<a href="#">112.005.000</a>
<a href="#">Pr 2.058-Ap 3.1</a>
<a href="#">113.016.000 - 1 Pcs = 8 M</a>
<a href="#">Winkel-Kf-0-Klemmflansch-F3;R-Profil-Std-0-Nbv-Istanbul-Turkiye</a>
<a href="#">200.056.000</a>
<a href="#">4.058 + Ap 3 Q</a>
<a href="#">200.007.000</a>
<a href="#">113.015.000</a>
<a href="#">Jt-Pa 1792/231.203.001</a>
<a href="#">200.002.000</a>
<a href="#">113.011.000 L=3600mm</a>
<a href="#">4.058</a>
<a href="#">1319.40.08-00-4</a>
<a href="#">113.015.001</a>
<a href="#">200.001.000, 4.054 Winkel-Rolle Å216; 62,5 Mm</a>
<a href="#">206.039.000</a>
<a href="#">Ap3-Q</a>
<a href="#">200.008.000, 4.061 Winkel-Rolle Å216; 107,7 Mm</a>