

Winkel

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Winkel Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Winkel T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
200.012.000	4.073 WINKEL bearing Ø 70.1 mm Can be adjusted axially via discs
Axial roller bearing WINKEL type 4.063 + AP	
Guide profile WINKEL Standard	6NbV L=3200mm (Standard 6NbV L3200 with holes for mounting M16)
Bogen 90° 1/2" AG IG	WINKEL 90Grd AuŐen/Innengewinde 1/2" ohne Bund Art.Nr.: CU3092MS.1/2
200.216.306	3.063 Heavy Duty ANGLE roller Delivery includes - 1 grease nipple M6 x 1 - 1 O-ring - 2 sealing washers 0.5 mm
200.216.304	3.061 Heavy Duty WINKEL roller Delivery includes - 1 grease nipple M6 x 1 - 1 O-ring - 2 sealing washers 0.5 mm
113.016.000	8,96 m U-Profil Standard 6 NbV WINKEL guide profile Number Length 2 4,480.00 mm External dimensions: 201.5 x 71.2 mm Chamber dimensions: 150.1 mm Sandblasted with SA 2.5 blasting pattern Original hot-rolled WINKEL profiles are made from S450 J2 mod. The significantly improved material has

	high strength properties and thus enables a higher load between the roller and the profile. Our sawing tolerances are - up to a length of 2,999 mm ± 1 mm - from a length of 3,000 mm ± 2 mm
113.014.000	113.014.000 U-Profil Standard 4 NbV WINKEL guide profile Number Length 2 3,500.00 mm External dimensions: 157.2 x 61.2 mm Chamber dimensions: 108.4 mm Sandblasted with SA 2.5 blasting pattern Original hot-rolled WINKEL profiles are made from S450 J2 mod. The significantly improved material has high strength properties and thus enables a higher load between the roller and the profile. Our sawing tolerances are - up to a length of 2,999 mm ± 1 mm - from a length of 3,000 mm ± 2 mm
113.016.000	
200.216.304	
200.216.306	
113.014.000	
200.056.000	4.063 + AP 6 ANGLE roller Ø 149.0 mm ANGLE roller permanently welded with screwing plate Screwing plate rectangular 200 x 150 x 20 mm
113.016.000	U-profile standard 6 NbV ANGLE guide profile Number Length 2 7,000.00 mm External dimensions: 201.5 x 71.2 mm Chamber dimensions: 150.1 mm Sandblasted with blasting pattern SA 2.5
3199 10 21	
113.001.000	
113.010.000 0 Nbv Aussenmaã223;E 86,5 X 36 Mm Anzahl Lã196;Nge 4 1.000,00 Mm Sandgestrahlt Mit Strahlbi	
4.062	
709370.51.00-01	
4.054+ap0	
113.010.000	
113.011.000 L=3000mm	
Hp10-2-Igf08n	
4.056	
200.055.001 4.061 + Ap 4 Q Kombirolle Å216; 107,7 Mm Fest Verschweiã223;T Mit Anschraubplatte Anschraubpl	
240.100.176	

Jt 2.058	200.210.303 - Ø 88,4 mm just. ANGLE roll unit
113.010.000 L=3040mm	
200.165.000	
113.010.000 L=4500mm	
96510.00.00-25-3	
1022.550.130/4/	
061.073.030	
227.044.000	
3199.06.17 Inkl Fda Zertifikat	
Kb 4.072 P	
Pa20080	
200.163.000	
231.002.000	
2.056	
4.073 Ap-1q	
113.010.000 L=1200mm	
1022.550128/4/	
113.012.001	
1319.40.06-00-3	
4.072p	
201.035.000	
3166.06.10	
200.105.000, Pr 4.062 Winkel-Rolle Ä216; 127,8 Mm	
3139.06.00	
4.058+ap3	
290.004.000	
113.015.002 Prã196;Zisionsprofil Pr 5 Nbv Aussenmaã223;E 175 X 64 Mm Anzahl Lã196;Nge 4 1.000,00 Mm	
113.014.000	
200.105.000 Pr 4.062 Kombirolle Ä216;	

127,8 Mm
200.101.002
Kb 4.073
3116.06.00
Jc 4.054
709370.41.00-01-4
3199.10.17
200.003.000
113.022.001
19439.01.02-02-3
290.003.000
Mr1942
200.076.001
205.064.000
200.001.000
212.004.000
Mr1941
U-Profil Standard 0 Nbv
113.013.000 Aussenmaã223;E 135,4 X 53 Mm Anzahl Lõ;Nge 2 10.000,00 Mm Sandgestrahlt Mit Strahlbild Sa 2,5 Gewicht 572,00 Kg
225.000.000(W2r.230.06.Xx 1106kd Dkol-10l)
200.015.002
205.062.000
3nb
113.014.000 4 Nbv Aussenmaã223;E 157,2 X 61,2 Mm Anzahl Lã196;Nge 4 1.000,00 Mm Sandgestrahlt Mit Strahl
3199.08.17
4.072 P
205.093.001
201.012.000

201.055.001
Ds-3-05
112.005.000
Pr 2.058-Ap 3.1
113.016.000 - 1 Pcs = 8 M
Winkel-Kf-0-Klemmflansch-F3;R-Profil-Std-0-Nbv-Istanbul-Turkiye
200.056.000
4.058 + Ap 3 Q
200.007.000
113.015.000
Jt-Pa 1792/231.203.001
200.002.000
113.011.000 L=3600mm
4.058
1319.40.08-00-4
113.015.001
200.001.000, 4.054 Winkel-Rolle Å216; 62,5 Mm
206.039.000
Ap3-Q
200.008.000, 4.061 Winkel-Rolle Å216; 107,7 Mm