

## Ytc

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Ytc** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Ytc Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">YT-2500LSI2301S</a>	Smart positioner YT-2500 Acting: Simple Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : 20...70 mm Air connection type : G1/4" Cable gland thread : G½" Communication: None Option: Feedback signal Temprature: -30 à 85°C Material : Aluminium Bracket included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
<a href="#">repair kit 310</a>	
<a href="#">YT-310</a>	Seri:31212729
<a href="#">YT-2500RSI5221S</a>	Smart positioner YT-2500 Acting: Single Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : Namur Air connection type : NPT1/4" Cable gland thread : ½" NPT Communication: HArtt Option: Feedback signal Temprature: -30 à 85°C Material : Aluminium Bracket included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : Diam 1 Connection type : PT1/4" Dome cover Option:

<a href="#">YT-1000RDN521S10</a>	Without Temp¼rate: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2.8 kg / 4.2 kg Dim : 27 x 20 x 20 cm
<a href="#">YT-1000RDN521S13</a>	Electro-Pneumatic positioner YT-1000 Rotary Acting: Simple Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : 2 Connection type : PT1/4" Dome cover Option : Limit switch (Internal) Temp¼rate: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
<a href="#">YT-1000RSN532S15</a>	Electro-Pneumatic positioner YT-1000 Rotary Acting: Simple Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : None Connection type : NPT1/4" Dome cover Option : Feedback signal + Limit switch (Internal) Temp¼rate: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
<a href="#">YT-310N1</a>	Volume booster YT-310 N1 Connection : NPT 3/4" Pressure maxi : 10 B Pressure signal : 7 B maxi Temp¼rate: -20 .. 70°C Material : Aluminium Net weight / Brut : 2.3 kg / 2.5 kg Dim : 18 x 14 x 14 cm Origine : South Korea Code HTS : 848110999
<a href="#">YT-1000RDN521S11</a>	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : 2 Connection type : PT1/4" Dome cover Option : Feedback signal Temp¼rate: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
<a href="#">YT-2501LSI2321S1</a>	Smart positioner YT-2501 - Linear Acting: Single Input signal : 4-20 mA Ex-proof : ATEX -Ex ia IIC T5/T6 Gb Lever : 20 ~70 mm Air connection type : NPT1/4" Cable gland thread : ½" G Communication: HART Option: Feedback signal Feedback module : SPTM Temp¼rate: -30 à 85°C Material : Aluminium No Included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
<a href="#">G1/4//YT-2500LSI2321S</a>	
<a href="#">YT-2500LSI2321S</a>	Smart positioner YT-2500 Acting: Single Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : 20...70 mm Air connection type : G 1/4" Cable gland thread : ½" G Communication: Hart Option: Feedback signal Temp¼rate: - 30 à 85°C Material : Aluminium
<a href="#">YT-3303RSN1201S</a>	Smart positioner YT-3300 Acting: Double Input signal : 4-20 mA Ex-proof : without Lever: M6 X 34 L Connection type : N1/4" Cable gland thread : ½" G Communication: HART Option: Without Temp¼rate: -30 à 85°C Material : Aluminium Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
<a href="#">YT-3400RDC5103S</a>	Smart positioner YT-3400 Acting: Double Input signal : 4 ~20 mA Ex-proof : Exd IIC T6 Lever : Namur Connection type : Rc 1/4" Cable gland thread : ½" Communication: without Option: Feedback signal & limit switch ( Electronic version)

<a href="#">YT-2500RD12121S</a>	Temp¼rate: -30 à 85°C Smart positioner YT-2500 Acting: Double Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : M6 X 63 L Connection type : Rc 1/4" Cable gland thread : ½" G Communication: Hart Option: Feedback signal Temp¼rate: -30 à 85°C Material : Aluminium
<a href="#">YT-310N2</a>	Volume booster YT-310 N2 Connection : NPT 3/4" Pressure maxi : 10 B Pressure signal : 7 B maxi Temp¼rate: -20 ..120°C Matreial : Aluminium
<a href="#">Yt-400sn1</a>	
<a href="#">Yt-205an110</a>	
<a href="#">Yt-1000rdn521s10</a>	
<a href="#">Yt-2500lsi1321s</a>	
<a href="#">Yt-200an01</a>	
<a href="#">Yt-310n1</a>	
<a href="#">Yt-3300ldn4201s</a>	
<a href="#">Yt-1000ldi111s0</a>	
<a href="#">Yt-520s21</a>	
<a href="#">Model: Yt-2500, Lsn2221 S</a>	
<a href="#">Yt-200bn010</a>	
<a href="#">Yt-200bn210</a>	
<a href="#">Yt-320n1,Pro. Å:12fa2,Max Air: 1mpa,Npt 1/2</a>	
<a href="#">Yt-300 Not Complete</a>	
<a href="#">Yt-520d22</a>	
<a href="#">Yt-320n1</a>	
<a href="#">Yt-1000rdm522s10</a>	
<a href="#">Yt-1000ldm231s0</a>	
<a href="#">E / P Switch Positioner For Model : Yt 1000 Rdn 52110</a>	
<a href="#">Yt-1000 Ldm231so S/N:K0513997</a>	
<a href="#">Repair Kit For Yt-310</a>	
<a href="#">Yt-1000rdn521s13</a>	
<a href="#">Yt-300p1</a>	
<a href="#">Yt-300 Volume-Enhancing, Repair And</a>	

<a href="#">Maintenance Kit</a>	
<a href="#">Yt-200</a>	
<a href="#">Yt-2500lsi1322s</a>	
<a href="#">E / P Positioner For Model : Yt 1000 Rdn 52110</a>	
<a href="#">Yt-850m411</a>	
<a href="#">Yt-300n1</a>	
<a href="#">Yt-1000 Rdn13114 Ra - , By Yt-1000 Rdn131s14</a>	
<a href="#">Yt-1000lsm111s3</a>	
<a href="#">Yt-200 Repair Kit For Air Filter Regulator</a>	
<a href="#">Yt-310n</a>	
<a href="#">Yt-320-N2</a>	
<a href="#">Yt-2500lsn120 4s</a>	
<a href="#">Yt-1000rdn531s13</a>	
<a href="#">Electro Pneumatik Rotary Positioner Yt-1000 Rdm</a>	S/N 12051781 1 set will be use with 4 " butterfly valve and 1 set will be use with 3" Butterfly valve Please see attached Photo
<a href="#">Yt-3450</a>	