

Ytc

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Ytc** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Ytc Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
YT-2500LSI2301S	Smart positioner YT-2500 Acting: Simple Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : 20...70 mm Air connection type : G1/4" Cable gland thread : G½" Communication: None Option: Feedback signal Temprature: -30 à 85°C Material : Aluminium Bracket included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
repair kit 310	
YT-310	Seri:31212729
YT-2500RSI5221S	Smart positioner YT-2500 Acting: Single Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : Namur Air connection type : NPT1/4" Cable gland thread : ½" NPT Communication: HArtt Option: Feedback signal Temprature: -30 à 85°C Material : Aluminium Bracket included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : Diam 1 Connection type : PT1/4" Dome cover Option:

YT-1000RDN521S10	Without Temp¼rate: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2.8 kg / 4.2 kg Dim : 27 x 20 x 20 cm
YT-1000RDN521S13	Electro-Pneumatic positioner YT-1000 Rotary Acting: Simple Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : 2 Connection type : PT1/4" Dome cover Option : Limit switch (Internal) Temp¼rate: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
YT-1000RSN532S15	Electro-Pneumatic positioner YT-1000 Rotary Acting: Simple Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : None Connection type : NPT1/4" Dome cover Option : Feedback signal + Limit switch (Internal) Temp¼rate: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
YT-310N1	Volume booster YT-310 N1 Connection : NPT 3/4" Pressure maxi : 10 B Pressure signal : 7 B maxi Temp¼rate: -20 .. 70°C Material : Aluminium Net weight / Brut : 2.3 kg / 2.5 kg Dim : 18 x 14 x 14 cm Origine : South Korea Code HTS : 848110999
YT-1000RDN521S11	Electro-Pneumatic positioner YT-1000 Rotary Acting: Double Signal : 4-20 mA Ex-proof : None Lever : Namur Orifice type : 2 Connection type : PT1/4" Dome cover Option : Feedback signal Temp¼rate: -20 à 70°C Material : Aluminium Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 3.6 kg / 4.5 kg Dim : 30 x 20 x 30 cm
YT-2501LSI2321S1	Smart positioner YT-2501 - Linear Acting: Single Input signal : 4-20 mA Ex-proof : ATEX -Ex ia IIC T5/T6 Gb Lever : 20 ~70 mm Air connection type : NPT1/4" Cable gland thread : ½" G Communication: HART Option: Feedback signal Feedback module : SPTM Temp¼rate: -30 à 85°C Material : Aluminium No Included Origine : South Korea Code HTS : 8481109990 Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
G1/4//YT-2500LSI2321S	
YT-2500LSI2321S	Smart positioner YT-2500 Acting: Single Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : 20...70 mm Air connection type : G 1/4" Cable gland thread : ½" G Communication: Hart Option: Feedback signal Temp¼rate: - 30 à 85°C Material : Aluminium
YT-3303RSN1201S	Smart positioner YT-3300 Acting: Double Input signal : 4-20 mA Ex-proof : without Lever: M6 X 34 L Connection type : N1/4" Cable gland thread : ½" G Communication: HART Option: Without Temp¼rate: -30 à 85°C Material : Aluminium Net weight / Brut : 2 kg / 3,9 kg Dim : 27 x 20 x 20 cm
YT-3400RDC5103S	Smart positioner YT-3400 Acting: Double Input signal : 4 ~20 mA Ex-proof : Exd IIC T6 Lever : Namur Connection type : Rc 1/4" Cable gland thread : ½" Communication: without Option: Feedback signal & limit switch (Electronic version)

YT-2500RD12121S	Temp¼rate: -30 à 85°C Smart positioner YT-2500 Acting: Double Input signal : 4-20 mA Ex-proof : Ex ia IIC T5/T6 Lever : M6 X 63 L Connection type : Rc 1/4" Cable gland thread : ½" G Communication: Hart Option: Feedback signal Temp¼rate: -30 à 85°C Material : Aluminium
YT-310N2	Volume booster YT-310 N2 Connection : NPT 3/4" Pressure maxi : 10 B Pressure signal : 7 B maxi Temp¼rate: -20 ..120°C Matreial : Aluminium
Yt-400sn1	
Yt-205an110	
Yt-1000rdn521s10	
Yt-2500lsi1321s	
Yt-200an01	
Yt-310n1	
Yt-3300ldn4201s	
Yt-1000ldi111s0	
Yt-520s21	
Model: Yt-2500, Lsn2221 S	
Yt-200bn010	
Yt-200bn210	
Yt-320n1,Pro. Å:12fa2,Max Air: 1mpa,Npt 1/2	
Yt-300 Not Complete	
Yt-520d22	
Yt-320n1	
Yt-1000rdm522s10	
Yt-1000ldm231s0	
E / P Switch Positioner For Model : Yt 1000 Rdn 52110	
Yt-1000 Ldm231so S/N:K0513997	
Repair Kit For Yt-310	
Yt-1000rdn521s13	
Yt-300p1	
Yt-300 Volume-Enhancing, Repair And	

Maintenance Kit	
Yt-200	
Yt-2500lsi1322s	
E / P Positioner For Model : Yt 1000 Rdn 52110	
Yt-850m411	
Yt-300n1	
Yt-1000 Rdn13114 Ra - , By Yt-1000 Rdn131s14	
Yt-1000lsm111s3	
Yt-200 Repair Kit For Air Filter Regulator	
Yt-310n	
Yt-320-N2	
Yt-2500lsn120 4s	
Yt-1000rdn531s13	
Electro Pneumatik Rotary Positioner Yt-1000 Rdm	S/N 12051781 1 set will be use with 4 " butterfly valve and 1 set will be use with 3" Butterfly valve Please see attached Photo
Yt-3450	