

## Zeca



Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Zeca** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Zeca T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">1.000.820</a>	Automatic hose reel AML 100 (Plastic housing impact-resistant, UV-resistant) with 16m - 10mm ID PU compressed air hose, max. 15bar/40°C, 1.5m connection hose, Connection fittings NW 7.2, locking, wall bracket pivoting
<a href="#">4325RNF</a>	
<a href="#">4325</a>	
<a href="#">Trainline roller type 1730</a>	Equipment: 29 m cable H05 VV-F 4 x 4 qmm plus 2 m freely hanging Power: rolled up - 11 kW - 400 V unrolled - 15 kW - 400 V Dimensions: H x W x D = 530 x 440 x 365 mm Protection class: IP 65 Execution: - Direct mounting on the wall - special spring drive with high Resilience
<a href="#">6186/PRC/IP65</a>	Art-Nr.: 2.402.009 Automatic cable reel PR-C IP65 (cast aluminum housing) with 26m cable 3x1.5 mm² H05VV-F, max. 500 V, 1.1/1.8KW, IP65, slip ring 10A, wall bracket pivotable

<a href="#">2.250.006</a>	Automatic cable reel X 4000 (plastic housing) with 10m cable H05VV-F 3x2.5 mm <sup>2</sup> , 220V (test load: 500V), max. 1.9/2.5KW, IP42, 2m connection cable with Rubber Schuko connections, thermal fuse, Locking device, swiveling wall bracket
<a href="#">2.580.703</a>	Fix mounting bracket for cable reel IE 1700
<a href="#">2.580.704</a>	Roller guide reversible (width 160mm)
<a href="#">2.582.782</a>	1782 Automatic cable reel IE 1700 (steel, aluminum housing) with 8m cable H05VV-F 16x2.5 mm <sup>2</sup> , max. 7.5A, slip ring 32A, protection class IP65, 2m connection cable, Detent, side mounting flange, type 1
<a href="#">6628</a>	Balancer from the PR series with steel cable. Further information is on the data sheet. Attention: Special order, no returns possible not a listed item.
<a href="#">2.582.773</a>	Automatic cable reel IE 1700 (steel, aluminum housing) with 53m cable H05VV-F 10x1.5 mm <sup>2</sup> , max. 4.5A, Slip ring 16A, protection class IP65, 2m connection cable, without locking, side mounting flange, type 2
<a href="#">2.300.005</a>	Automatic cable reel MAGNUM 7000 (plastic housing) with 27m cable H05VV-F 4x1.5mm <sup>2</sup> , 500V, max. 1.1/1.8KW, IP 42, locking, wall mount pivotable
<a href="#">2.300.003</a>	Automatic cable reel MAGNUM 7000 (plastic housing) with 27m cable H05VV-F 3x1.5mm <sup>2</sup> , max. 220V (test load: 500V), 1.1/1.8KW, IP42, 2m cable with Schuko connections, Locking, wall bracket swiveling
<a href="#">2.250.006</a>	Automatic cable reel X 4000 (plastic housing) with 10m cable H05VV-F 3x2.5 mm <sup>2</sup> , 220V (test load: 500V), max. 1.9/2.5KW, IP42, 2m connection cable with rubber Schuko connections, thermal fuse, lock, swivel wall bracket - corresponds to Zeca 4325
<a href="#">Am58/Am8</a>	
<a href="#">6619prc</a>	
<a href="#">370/10</a>	
<a href="#">1.000.821 Automatik Schlauchaufroller Aml 200</a>	
<a href="#">4315</a>	
<a href="#">2.408.009 Automatik Kabelaufroller Pr-L</a>	
<a href="#">6175 Prc</a>	
<a href="#">Art328/10 230v</a>	
<a href="#">5000 Series - Am8</a>	
<a href="#">1.000.821 Automatik Schlauchaufroller</a>	

<a href="#">1735</a>
<a href="#">040630-03x1,5(Ex. 6186)</a>
<a href="#">Balancer With Anti-Fall Device 634</a>
<a href="#">804/8</a>
<a href="#">6069/Prc</a>
<a href="#">Cv2501x4grmt</a>
<a href="#">107a1 9003</a>
<a href="#">117a1 9003</a>
<a href="#">208 Detektor, Prüfgerät Für Batterien</a>
<a href="#">5908/360</a>
<a href="#">207 Battery Tester</a>
<a href="#">945</a>