

Zeppelin

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Zeppelin Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Zeppelin T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
20003181	
20003183	
201214946	
20374466	
APN 500/96 GS	
F805	
F811	
F812	
20499684	Filter cartridge 2.5m ² Ø160x1000 PES-Al Outer diameter: 185mm Length: 1000mm Filter material: polyester fleece with aluminum coating Shape: conical Addition: Electrically conductive and food-approved
20356629	Filter cartridge 2.4m ² Ø143x1000 PES/Al Outer diameter: 153mm Length: 1000mm Filter material: spunbonded polyester, aluminized

	Filter attachment: bayonet flange Shape: conical Electrically Conductive: Yes Food suitability: Yes
20356636	Filter cartridge 2.4m ² Ø143x1000 PES/PTFE Outer diameter: 153mm Length: 1000mm Filter material: Polyester spun fleece with ePTFE membrane Filter attachment: bayonet flange Shape: conical Electrically Conductive: Yes Food suitability: Yes
20356608	Filter cartridge 1.0m ² Ø127x600 Baj. PES AL Outer diameter: 135mm Length: 600mm Filter material: polyester fleece with aluminum coating Filter attachment: bayonet Shape: conical Electrically Conductive: Yes Food suitability: Yes
20499693	Rotary Valve APN 500/96.0 GS Discharge Rotary Valve for middle pressure applications ***** As spare for serial-no. 60113, order 3000007616 (year 2013) ***** Serial number / TAG number XXXXX / none General data product: Petcoke, carbon dust bulk density: 350 - 600 kg/m ³ capacity: approx. 4,3 - 43 t/h rotor speed: approx. 1,7 - 28,7 RPM system pressure inlet: atmospheric system pressure outlet: max. + 0,7 bar g product temperature: max. +80°C ambient temperature: -10 - +40°C 950 Installation site: PLEASE SPECIFY ? Turkey? Export control? Altitude: PLEASE SPECIFY >mNN
Membrane D194,H23,NR/SBR-PA	