

Zimmer Group



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Zimmer Group Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Zimmer Group Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Rbps2000-A	Serie 101240
Lcp-2505ak-08	
ZIMM TYP-MSZ-50-S İ=28-1 1800 MİN MSZ-50-S-2E NR=	837114
MKS2501A	
MKS2005AK	Clamping element pneumatic Holding force: 600.0 N Holding force PLUS: 1300.0 N theoretical holding force PLUS: 1600.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 5.5 bar State: passive (NC) RoHS Compliant: Yes CE marking: Yes
MK3502K-03	Pneumatic clamping element Holding force: 2000.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 2.0 bar State: active (NO) Scraper: No. Other: clearance height RoHS Compliant: Yes
MK3502K	JD157AJ
M14X1.5S-104	

M20X1.5M-110	
MKS3505AK	Clamping element pneumatic Holding force: 1250.0 N Holding force PLUS: 2200.0 N Theoretical holding force PLUS: 2750.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 5.5 bar State: passive (NC) RoHS Compliant: Yes CE marking: Yes
MBPS 2001 GS1A Zimmer	Clamp
MKS2505AR	Clamping element pneumatic
MK 3001 A	Clamp MK 3001 A Linear
MK 2501 A	Clamp MK 2501 A Linear
M14x1.5S 401	
M20X1.5M 110	
Klemme MKS 4501 A M5 Zimmer	Linear
ROTASCLEEN TG13	seri: 5773m1 ELERO JUNIOR 1S FİLE AKTUATÖR MOTOR
GPP5008N-AL-A	2-jaw parallel gripper pneumatic Nominal operating pressure: 6 bar Stroke per jaw: 8.0 mm Gripping force when opening: 560.0 N Gripping force when closing: 520.0 N
MKS2505KB	Clamping element pneumatic RoHS Compliant: Yes Holding force: 750 N Holding force PLUS connection: 1950 N Nominal operating pressure: 6.0 bar Operating pressure min .: 5.5 bar State: passive (NC)
RBPS2000-A	Pneumatic clamping and braking element RoHS Compliant: Yes Holding force: 10000 N Operating pressure min .: 4.0 bar State: passive (NC) Shaft Ø: 20.00 mm Scraper: Yes Sensor connection: query groove
HM1030NC	
mk3505ak AB00204218AG	
GK 20 N-B	Gripper GK 20 N-B Zimmer handling element
MK2502K	
M14X1.5S-104	
M20X1.5m-110	
MKS2001A	BJ-00414805
MGH8375	
MK5501A	
HK1501A	
SF74-180N-C	

DB314586AH	
MKR2500A	
BH777	
GP406N-C	handling element 2-jaw parallel gripper pneumatic Nominal working pressure: 6 bar Stroke per jaw: 6.0 mm Gripping force when opening: 325.0 N Gripping force when closing: 300.0 N Nominal gripping force: 300.0 N
MK3502K-03	
TKPWS 5505 AS1DA	JH/102700
GPP5035NC-00-A	handling element 2-jaw parallel gripper pneumatic Nominal working pressure: 6 bar Stroke per jaw: 35.0 mm Gripping force when closing: 8000.0 N Min. spring secured gripping force: 1900 N Nominal gripping force: 8000.0 N
SF155-180N-C	handling element flat swivel unit pneumatic Nominal working pressure: 6 bar Pan Angle: 180° Torque: 62.0 Nm
GK35N-B	
Gripper GP 406NC-C Zimmer	Your item no. GP406NC-C Nominal operating pressure: 6 bar, Stroke per jaw: 6.0 mm, Gripping force when closing: 400 N, Gripping force secured by spring min.: 100 N, Gripping force: 300N - 950N
MK1501A	
M20x1,5M-110	
M14x1.5S-104	
MBPS2004BS1	
EB5025ST	
GPP5025N-24-A	
Mk3502k-03	Jh00192046 ag
1943293	
M27X3S-109	Damper
4482832 - PP WINDER	SCHNEIDER MAGNETIC SWITCH MFS204 SKHC 211044
MK3505AK	
Brake element RBPS2500A	Clamping elements RoHS Compliant: Yes REACH compliant: Yes PLUS connection possible: No Min. operating pressure: 4.0 bar Min. operating pressure: 4.0 bar Holding torque: 140 Nm Scraper: Yes Cylinder volume per cycle: 280 cm³ Shaft Ø: 25.00 mm Sensor connection: query groove Holding torque: 140 Nm Scraper: Yes Cylinder volume per cycle: 280 cm³ Sensor connection: query groove Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Operating

	temperature max.: 70 °C
MGP806N	
MKS2502K	
E050-08-147	Self-closing Silento Doppio RoHS Compliant: Yes REACH compliant: Yes Stroke: 50.0 mm, medium: fluid Type: self-closing Mass to be braked: 50.0 kg Direction of action: closing on both sides, without freewheel Freewheel length: 0.0 mm SEZ color housing: gray RAL7035 SEZ locking lever color: natural Total length max.: 237.0 mm SEZ hole spacing: 224.0 mm SEZ Ø holes: 4.2 mm SEZ width: 12.2mm SEZ height: 17.8mm SEZ locking lever design: Type S SEZ connection drilling: Cross drilling with countersink SEZ spring force F1: 17.0 N SEZ spring force F2: 28.0 N
S000-00-024	Aktivator Universal
LS16-25	
PHE16X15LMDD-A	PowerStop Industrial shock absorbers RoHS Compliant: Yes REACH compliant: Yes Series: High Energy Head: without head, short piston rod Protection: without protection Fixed stop: Yes Number of lock nuts: 1 Stroke max.: 20 mm Adjustability: No
GPD5013N-00-A	3-jaw centric gripper pneumatic RoHS Compliant: Yes REACH compliant: Yes Nominal operating pressure: 6 bar Stroke per jaw: 13.0 mm Gripping force when opening: 3910.0 N Gripping force when closing: 3770.0 N
TPC-AS59X58M	Structural damper BasicStop
GS65-B	O-ring assembly gripper pneumatic RoHS Compliant: Yes REACH compliant: Yes Spreading stroke per jaw adjustable min.: 3.0 mm Spreading stroke per jaw adjustable max.: 6.0 mm Wiping stroke: 5.0 mm
GD308NC-C	
GPP5025N-24-A	
KWH3512ES1A-A	
HK2001G	
UBPS 5503 AS1L/02	
HK2001A	
MK2001A	
MK3505AK	
MGP803N	
MGP803NC	
HK4501A	

MKR3000A	
MFS01-S-KHC-P1-PNP	
Gripper GK 20 N-B	
RBPS2000-A	
GVAG2VK3RU	GVAG-2VK3RU Level probe Probe (2 electrodes) Size: G 1" Temp.: max.120C° Pressure: max.10 bar Housing: 1.4305 Electrodes: 1.4571 Coating: PVDF Sealing rings: FPM Electrical connection: 4-pin device plug DIN 43650 A (protection class IP65) Contact assignment: contacts 1,2+3 are used, Reference terminal contact on housing = contact 3 Teflon sockets: electrodes/housing Special feature: uncast, protection class of the unit similar to IP40, Product label without mention of protection class Lengths in mm: 40; 40 Material: electrode VA/K
120.073.01.009.1 JZ, NO.FT-101	PRINTING HEAD BEARING FOR LEFT-RIGHT SIDES
120.512.03.01.001.1	BRUSHING ROLLER 120.512.03.01.001.1 CONSTRUCT. WIDTH 3245 MM ARTICLE NO54015
7364 1" A-33867	NIPPLE "NITO"
12.503.30.3.4.BF17	LENZE REDUKTOR TYPE
GH7665	
GH76100	
MGH8350	
MGH83100	
MKS2501A	
HK3001A	
MKRS5000A-06	BJ-00407680
WER3000FSI19-09-A	BC-00654493
Mk3502k-03	
SF50-180D4-C	
SF50-180D4-C	
HK1501A	
Mk2502k	Clamping element pneumatic Holding force: 1200.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 2.0 bar State: active (NO) RoHS Compliant: Yes
Mk3505ak	clamping element pneumatic Holding force: 2000.0 N Nominal operating pressure: 6.0 bar Min. Operating pressure: 2.0 bar State: active (NO) RoHS Compliant: Yes Reach compliant:

Yes

[Mks2505kb](#)

clamping element Pneumatic DE 84 79 90 70 Holding force:
750.0 N Holding force PLUS: 1950,0 N theoretical holding
force PLUS: 2400.0 N Nominal operating pressure: 6,0bar
operating pressure: 5.5 bar RoHs; yes CE: Yes