



Zöllner Signal

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim süresi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Zöllner Signal Markası, tedarik süresi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Zöllner Signal T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
01031441	Spare part set Makrofon M75F/260 membrane Drawing 01031441
00171643	Servo solenoid valve ZVE Voltage 230VAC Drawing 017164
00171644	Servo solenoid valve ZVE Voltage 24VDC Drawing 017164
017142	Gasket set ZVE valve Drawing 017142
017251171	Oval flange gasket M75F
017142	Gasket set ZVE valve Drawing 017142
0101672	Filter insert F3
0104298067	Macrophone system M75F/370 ZVEH Class III + IV - type tested Drawing 06100087 for compressed air Main current for tripping 230V AC 24 watts Heating device 230V AC 30 watts Protection class IP56 Weight approx. 8 kg
01049321	Filter F3.1 stainless steel with drain tap Drawing 01415303
	Signal machine 6+S Type "B" - type-tested Data sheet

014151181	06100090 Connection plan 01506297223 for voltage 230 V max. 90 watts (standby 4.95 watts) with black front panel 144 x 96 mm five signals according to rule 35 (a,b,c,e,g) of the KVR 1972 (Colreg 72) + SOS Protection class IP23 Weight approx. 0.9 kg
Signal direction detector SRD414/4	- Elephant Ears - publication SW 116.1 Voltage 24 V DC (4 W) according to 96/98/EC Annex A.1, item No. A.1/4.58 and Annex B, Module B, SOLAS 74 as amended, Reg. V/18,V/19 & X/3, IMO Res. A.694(17), 2000 HSC Code, IMO Res. MSC86(70) & 191(79) Connection cable CAT5/7 (not included) consisting of: 1 microphone unit SRD414/4 Drawing 01415556 made of stainless steel, 5 microphones 1x connector RJ45c-P4SAS Protection class IP 56 Weight: 6.7 kg 1 control unit SRD 414/4 Drawing 01415651 Connection plan 01506741 Dimensions 144 x 144 mm with 8 LEDs for direction indication Speaker for acoustic Playback with dimmer and volume control Protection class IP22 Weight: 1.6 kg
126-0-00-4	D9923 MEMBRAN, SIGNALHORN
01031441	First division kit Makrofon M75F / 260 diaphragm Weight: 0.05 kg
Si710/0-03/5	D9923 MEMBRAN, SIGNALHORN
889007040	D9923 MEMBRAN, SIGNALHORN
Si126-0-00-4	D9923 MEMBRAN, SIGNALHORN
Si3689	D9923 MEMBRAN, SIGNALHORN
Si710-0-03-5	D9923 MEMBRAN, SIGNALHORN
01126000	Membrane TM125/3-fach
12600	D9923 MEMBRAN, SIGNALHORN
Si126/0-00/4	D9923 MEMBRAN, SIGNALHORN
01.126000	D9923 MEMBRAN, SIGNALHORN
71003	D9923 MEMBRAN, SIGNALHORN